

Package ‘localModel’

October 13, 2022

Title LIME-Based Explanations with Interpretable Inputs Based on Ceteris Paribus Profiles

Version 0.5

Maintainer Przemyslaw Biecek <przemyslaw.biecek@gmail.com>

Description Local explanations of machine learning models describe, how features contributed to a single prediction.
This package implements an explanation method based on LIME (Local Interpretable Model-agnostic Explanations, see Tullio Ribeiro, Singh, Guestrin (2016) <[doi:10.1145/2939672.2939778](https://doi.org/10.1145/2939672.2939778)>) in which interpretable inputs are created based on local rather than global behaviour of each original feature.

URL <https://github.com/ModelOriented/localModel>

BugReports <https://github.com/ModelOriented/localModel/issues>

Depends R (>= 3.5)

License GPL

Encoding UTF-8

Imports glmnet, DALEX, ggplot2, partykit, ingredients

RoxygenNote 7.1.1

Suggests covr, knitr, rmarkdown, randomForest, testthat

VignetteBuilder knitr

NeedsCompilation no

Author Przemyslaw Biecek [aut, cre],
Mateusz Staniak [aut],
Krystian Igras [ctb],
Alicja Gosiewska [ctb],
Harel Lustiger [ctb],
Willy Tadema [ctb]

Repository CRAN

Date/Publication 2021-09-14 16:50:01 UTC


```
# In this case each simulated observation has weight
# that is small when the distance from original observation is large,
# so closer observation have more weight.
model_lok
plot(model_lok)
```

identity_kernel	<i>LIME kernel that treats all observations as equally similar to the observation of interest.</i>
-----------------	--

Description

Kernels are meant to be used as an argument to `individual_surrogate_model` function. Other custom functions can be used. Such functions take two vectors and return a single number.

Usage

```
identity_kernel(explained_instance, simulated_instance)
```

Arguments

```
explained_instance      explained instance
simulated_instance     new observation
```

Value

```
numeric
```

Examples

```
library(DALEX)
library(randomForest)
library(localModel)
data('apartments')
mrf <- randomForest(m2.price ~., data = apartments, ntree = 50)
explainer <- explain(model = mrf,
                    data = apartments[, -1])
model_lok <- individual_surrogate_model(explainer, apartments[5, -1],
                                       size = 500, seed = 17,
                                       kernel = identity_kernel)

# In this case each simulated observation has equal weight
# when explanation model (LASSO) is fitted.
model_lok
plot(model_lok)
```

 individual_surrogate_model

LIME-like explanations based on Ceteris Paribus curves

Description

This function fits a LIME-type explanation of a single prediction. Interpretable binary features that describe the local impact of features on the prediction are created based on Ceteris Paribus Profiles. Then, a new dataset of similar observations is created and black box model predictions (scores in case of classification) are calculated for this dataset and LASSO regression model is fitted to them. This way, explanations are simplified and include only the most important features. More details about the methodology can be found in the vignettes.

Usage

```
individual_surrogate_model(
  x,
  new_observation,
  size,
  seed = NULL,
  kernel = identity_kernel,
  sampling = "uniform",
  ...
)
```

Arguments

<code>x</code>	an explainer created with the function <code>DALEX::explain()</code> .
<code>new_observation</code>	an observation to be explained. Columns in should correspond to columns in the data argument to <code>x</code> .
<code>size</code>	number of similar observation to be sampled.
<code>seed</code>	If not <code>NULL</code> , seed will be set to this value for reproducibility.
<code>kernel</code>	Kernel function which will be used to weight simulated observations.
<code>sampling</code>	Parameter that controls sampling while creating new observations.
<code>...</code>	Additional arguments that will be passed to <code>ingredients::ceteris_paribus</code> .

Value

data.frame of class `local_surrogate_explainer`

Examples

```
# Example based on apartments data from DALEX package.
library(DALEX)
library(randomForest)
library(localModel)
data('apartments')
mrf <- randomForest(m2.price ~., data = apartments, ntree = 50)
explainer <- explain(model = mrf,
                    data = apartments[, -1])
model_lok <- individual_surrogate_model(explainer, apartments[5, -1],
                                       size = 500, seed = 17)

model_lok
plot(model_lok)
```

localModel

localModel: LIME-like explanations with interpretable features based on Ceteris Paribus profiles

Description

This package implements LIME-like explanation method (see Tulio Ribeiro, Singh, Guestrin (2016) <doi:10.1145/2939672.2939778>) in which interpretable inputs are created based on local rather than global behaviour of each original feature.#'

Important functions

`individual_surrogate_model` generates an explanation for a single prediction with interpretable features based on Ceteris Paribus profiles. `plot.local_surrogate_explainer` plots the explanation.

`plot.local_surrogate_explainer`

Generic plot function for local surrogate explainers

Description

Generic plot function for local surrogate explainers

Usage

```
## S3 method for class 'local_surrogate_explainer'
plot(x, ..., geom = "bar")
```

Arguments

x	object of class local_surrogate_explainer
...	other objects of class local_surrogate_explainer. If provided, models will be plotted in rows, response levels in columns.
geom	If "point", lines with points at the end will be plotted, if "bar", bars will be plotted and if "arrow", arrows.

Examples

```
# Example based on apartments data from DALEX package.
library(DALEX)
library(randomForest)
library(localModel)
data('apartments')
mrf <- randomForest(m2.price ~., data = apartments, ntree = 50)
explainer <- explain(model = mrf,
                    data = apartments[, -1])
model_lok <- individual_surrogate_model(explainer, apartments[5, -1],
                                       size = 500, seed = 17)

model_lok
plot(model_lok)
```

plot_interpretable_feature

Plot Ceteris Paribus Profile and discretization

Description

Plot Ceteris Paribus Profile and discretization

Usage

```
plot_interpretable_feature(x, variable)
```

Arguments

x	local_surrogate_explainer object
variable	chr, name of the variable to be plotted

Value

ggplot2 object

```
print.local_surrogate_explainer
```

Generic print function for local surrogate explainers

Description

Generic print function for local surrogate explainers

Usage

```
## S3 method for class 'local_surrogate_explainer'  
print(x, ...)
```

Arguments

x	object of class local_surrogate_explainer
...	currently ignored

Examples

```
# Example based on apartments data from DALEX package.  
library(DALEX)  
library(randomForest)  
library(localModel)  
data('apartments')  
mrf <- randomForest(m2.price ~., data = apartments, ntree = 50)  
explainer <- explain(model = mrf,  
                     data = apartments[, -1])  
model_lok <- individual_surrogate_model(explainer, apartments[5, -1],  
                                       size = 500, seed = 17)  
  
plot(model_lok)  
model_lok
```

Index

`gaussian_kernel`, [2](#)

`identity_kernel`, [3](#)

`individual_surrogate_model`, [4](#), [5](#)

`localModel`, [5](#)

`plot.local_surrogate_explainer`, [5](#), [5](#)

`plot_interpretable_feature`, [6](#)

`print.local_surrogate_explainer`, [7](#)