

Package ‘OmopConstructor’

February 9, 2026

Title Build Tables in the OMOP Common Data Model

Version 0.2.0

Description Provides functionality to construct standardised tables from health care data formatted according to the Observational Medical Outcomes Partnership (OMOP) Common Data Model. The package includes tools to build key tables such as observation period and drug era, among others.

License Apache License (>= 2)

Encoding UTF-8

RoxygenNote 7.3.3

Imports cli, clock, dplyr, glue, omopgenerics, PatientProfiles, purrr, rlang

Depends R (>= 4.1)

Suggests bookdown, CDMConnector, duckdb, ggplot2, gt, knitr, odbc, omock, OmopSketch, rmarkdown, RPostgres, stringr, testthat (>= 3.0.0), tidyr, visOmopResults

Config/testthat/edition 3

URL <https://ohdsi.github.io/OmopConstructor/>

BugReports <https://github.com/ohdsi/OmopConstructor/issues>

VignetteBuilder knitr

NeedsCompilation no

Author Martí Català [aut, cre] (ORCID: <https://orcid.org/0000-0003-3308-9905>),
Elin Rowlands [ctb] (ORCID: <https://orcid.org/0009-0005-5166-0417>),
Cecilia Campanile [ctb] (ORCID: <https://orcid.org/0009-0007-6629-4661>)

Maintainer Martí Català <marti.catalasabate@ndorms.ox.ac.uk>

Repository CRAN

Date/Publication 2026-02-09 22:10:02 UTC

Contents

buildDrugEra	2
buildObservationPeriod	3
collapseRecords	4
Index	5

buildDrugEra	<i>Build the drug_era table</i>
--------------	---------------------------------

Description

Build the drug_era table

Usage

```
buildDrugEra(cdm, collapseDays = 30L)
```

Arguments

- cdm A cdm_reference object.
- collapseDays Number of days that two exposures can be separated to be collapsed in a single era.

Value

The lazy drug_era table.

Examples

```
library(omock)
library(OmopConstructor)
library(dplyr, warn.conflicts = TRUE)

cdm <- mockCdmFromDataset(datasetName = "GiBleed", source = "duckdb")

cdm$drug_era <- buildDrugEra(cdm = cdm)
cdm$drug_era |>
  glimpse()
```

`buildObservationPeriod`*Build observation_period table from data recorded in the cdm_reference*

Description

Build observation_period table from data recorded in the cdm_reference

Usage

```
buildObservationPeriod(  
  cdm,  
  collapseDays = Inf,  
  persistenceDays = Inf,  
  dateRange = as.Date(c("1900-01-01", NA)),  
  censorAge = 120L,  
  recordsFrom = c("drug_exposure", "visit_occurrence"),  
  periodTypeConceptId = 32817L  
)
```

Arguments

<code>cdm</code>	A cdm_reference object.
<code>collapseDays</code>	Distance between records to be collapsed.
<code>persistenceDays</code>	Number of days added at the end of an observation period as persistence window.
<code>dateRange</code>	Range of dates to be considered. By default '1900-01-01' is used as start date, whereas for censor date the first available of <code>source_release_date</code> , <code>cdm_release_date</code> , and <code>Sys.Date()</code> will be used.
<code>censorAge</code>	Age to censor individuals if they reach a certain age. The last day in observation of the individual will be the day prior to their birthday.
<code>recordsFrom</code>	Tables to retrieve observation records from.
<code>periodTypeConceptId</code>	Choose the <code>observation_period_type_concept_id</code> that best represents how the period was determined. Accepted Concepts.

Value

The cdm_reference object with a new observation_period.

collapseRecords	<i>Collapse records of a cdm_table into episodes.</i>
-----------------	---

Description

Collapse records of a cdm_table into episodes.

Usage

```
collapseRecords(  
  x,  
  startDate,  
  endDate,  
  by,  
  gap = 0L,  
  toSummarise = character(),  
  name = NULL  
)
```

Arguments

x	A cdm_table object.
startDate	Column in x that points to the start date of the record.
endDate	Column in x that point to the end date of the record.
by	Columns in x that aggregate the records.
gap	Integer; distance allowed between two consecutive records to be collapsed.
toSummarise	Columns in x that we want to be keep, the different columns will be added up.
name	Name of the new cdm_table created.

Value

The x cdm_table with the records collapsed.

Index

`buildDrugEra`, [2](#)
`buildObservationPeriod`, [3](#)
`collapseRecords`, [4](#)