

Package ‘datasus’

September 5, 2026

Type Package

Title An Interface to Brazilian Public Health Data

Version 0.16.1

Description Retrieves public health data from the Department of Informatics ('DATASUS') of the Brazilian Unified Health System ('Sistema Unico de Saude', 'SUS') through its online tabulation service and open-data catalog. It covers the Mortality Information System ('SIM'), Live Birth Information System ('SINASC'), Hospital Information System of the Unified Health System ('SIH/SUS'), Outpatient Information System of the Unified Health System ('SIA/SUS'), National Register of Health Establishments ('CNES'), Notifiable Diseases Information System ('SINAN'), National Immunization Program ('PNI'), Cancer Information System ('SISCAN'), and Food and Nutrition Surveillance System ('SISVAN'). Contemporary sources from the 'OpenDataSUS' portal include Events Supposedly Attributable to Vaccination or Immunization ('ESAVI'), influenza-like illness notifications from 'e-SUS Notifica', individual vaccination doses, coronavirus disease 2019 (COVID-19) hospital occupancy, and record-level mortality, live-birth and hospital-admission microdata. Curated schemas, selective columns, multipart downloads and chunk processing support memory-efficient analysis of large files. The package also provides grouped epidemiological indicators, confidence intervals, population-denominator joins, epidemiological calendars, moving averages and direct age standardization. An offline reference from the Brazilian Institute of Geography and Statistics (IBGE) supports territorial codes, joins and completion of geographic time series.

License GPL-3

Encoding UTF-8

URL <https://github.com/rpradosiqueira/datasus>

BugReports <https://github.com/rpradosiqueira/datasus/issues>

Depends R (>= 4.1.0)

Imports datasusr (>= 0.1.0), httr2, jsonlite, readr, rvest, stringi, xml2

Suggests foreign, knitr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

RoxygenNote 8.0.0

NeedsCompilation no

Author Renato Prado Siqueira [aut, cre]

Maintainer Renato Prado Siqueira <rpradosiqueira@gmail.com>

Repository CRAN

Date/Publication 2026-09-05 13:10:02 UTC

Contents

datasus-package	4
adicionar_territorio	5
calcular_indicador	6
calcular_taxa	7
calendario_epidemiologico	8
cnes	8
completar_territorios	9
datasus_catalogo	11
datasus_dicionario	11
datasus_opcoes	12
datasus_padronizar	13
datasus_proveniencia	14
datasus_territorios	14
datasus_validar_esquema	15
esavi	16
esus_sindrome_gripal	17
extrair_codigo_ibge	18
financiamento_sus	19
intervalo_taxa	20
juntar_populacao	21
letalidade	22
media_movel	23
microdados_arquivos	24
microdados_baixar	25
microdados_catalogo	26
microdados_ler	27
normalizar_codigo_ibge	28
ocupacao_hospitalar	29
opendatasus_arquivos	30
opendatasus_baixar	31
opendatasus_catalogo	33
opendatasus_ler	34
opendatasus_processar	35
opendatasus_recursos	37

padronizar_idade	37
pni_doses	39
pni_imunizacoes	40
populacao_padrao	41
populacao_residente	42
proporcao	43
semana_epidemiologica	44
sia_producao	45
sih_microdados	46
sih_morbidade	46
sih_producao	48
sim	49
sim_evita10_bruf	50
sim_evita10_mun	52
sim_evita10_uf	55
sim_evitb10_bruf	57
sim_evitb10_mun	59
sim_evitb10_uf	62
sim_inf10_bruf	64
sim_inf10_mun	67
sim_inf10_uf	71
sim_microdados	74
sim_obt10_bruf	74
sim_obt10_mun	77
sim_obt10_uf	80
sinan	82
sinan_dengue	84
sinan_mpox	85
sinasc	86
sinasc_microdados	87
sinasc_nv_bruf	88
sinasc_nv_mun	90
sinasc_nv_uf	93
siscan	96
sisvan	97
sivep_gripe	98
taxa_incendencia	99
taxa_mortalidade	100
validar_codigo_ibge	101

datasus-package

datasus: Brazilian public health data

Description

‘datasus’ provides a stable interface to aggregated TABNET queries, OpenDataSUS resources, record-level DATASUS files, territorial references and epidemiological analysis helpers. Discovery functions can be used before any download, and local catalogs and transformations remain usable without network access.

Main workflow

Start with [datasus_catalogo()] for supported TABNET datasets, [opendatasus_catalogo()] for contemporary portal datasets, or [microdados_catalogo()] for raw DBC/DBF file families. Plan requests with [datasus_opcoes()], [opendatasus_recurso()], [opendatasus_arquivos()] or [microdados_arquivos()] before querying or downloading data.

Use [opendatasus_baixar()] and [microdados_baixar()] when another engine will read the files, or [opendatasus_ler()] and [microdados_ler()] for in-memory workflows. System-specific functions such as [sim()], [sinasc()], [sih_producao()] and [cnes()] provide concise entry points for common data products.

Reproducibility and validation

Downloaded objects carry source, consultation time, local path and checksum metadata retrievable with [datasus_proveniencia()]. Use [datasus_dicionario()] and [datasus_validar_esquema()] to inspect curated fields and detect missing or type-incompatible analysis fields. Cache paths use [tools::R_user_dir()] by default and can be changed with option ‘datasus.cache_dir’.

Compatibility

Historical ‘sim_*()’ and ‘sinasc_nv_*()’ functions remain available for existing scripts. Their public signatures are preserved; new workflows should prefer [sim()] and [sinasc()]. Network integrations are tested only by explicit or scheduled smoke tests, while regular package tests use local fixtures and mocks.

Author(s)

Maintainer: Renato Prado Siqueira <rpradosiqueira@gmail.com>

Authors:

- Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

Useful links:

- <https://github.com/rpradosiqueira/datasus>
- Report bugs at <https://github.com/rpradosiqueira/datasus/issues>

adicionar_territorio *Add territorial attributes to a data frame*

Description

Validates a territorial code column and appends the corresponding current IBGE names and hierarchy. Six-digit DATASUS municipality codes are converted to seven-digit IBGE codes. The function does not redistribute historical observations across boundary changes.

Usage

```
adicionar_territorio(  
  dados,  
  codigo,  
  nivel = c("municipio", "uf", "regiao"),  
  desconhecido = c("erro", "na"),  
  sobrescrever = FALSE  
)
```

Arguments

<code>dados</code>	A data frame.
<code>codigo</code>	Name of the territorial code column.
<code>nivel</code>	Territorial level: "municipio", "uf" or "regiao".
<code>desconhecido</code>	How to handle unknown values: "erro", "na" or "manter".
<code>sobrescrever</code>	Whether existing columns with catalog names may be replaced.

Value

'dados' with territorial columns appended.

Examples

```
dados <- data.frame(codmun = c("500270", "500370"), casos = c(10, 5))  
adicionar_territorio(dados, "codmun")
```

calcular_indicador	<i>Aggregate epidemiological indicators</i>
--------------------	---

Description

Aggregates numerator and denominator counts before calculating rates, proportions, ratios or case fatality. Rates use exact Poisson confidence intervals; proportions and case fatality use exact binomial intervals.

Usage

```
calcular_indicador(
  dados,
  numerador,
  denominador,
  grupo = NULL,
  tipo = c("taxa", "proporcao", "razao", "letalidade"),
  multiplicador = NULL,
  confianca = NULL,
  na_rm = FALSE,
  zero_denominador = c("na", "erro")
)
```

Arguments

<code>dados</code>	A non-empty data frame.
<code>numerador</code>	Name of the non-negative numerator column.
<code>denominador</code>	Name of the non-negative denominator column.
<code>grupo</code>	Optional character vector naming grouping columns.
<code>tipo</code>	Indicator type: "taxa", "proporcao", "razao" or "letalidade".
<code>multiplicador</code>	Positive scale factor. When omitted, defaults to 100,000 for rates, 100 for proportions and case fatality, and 1 for ratios.
<code>confianca</code>	Optional confidence level. Exact intervals are available for rates, proportions and case fatality, but not for ratios.
<code>na_rm</code>	Whether rows with a missing numerator or denominator should be removed pairwise within each group. A group containing no complete row remains missing.
<code>zero_denominador</code>	How to handle zero denominators: "na" returns 'NA', while "erro" stops.

Value

A data frame containing the grouping columns, aggregated 'numerador', aggregated 'denominador', 'indicador', and optional confidence limits.

Examples

```
dados <- data.frame(
  ano = c(2024, 2024, 2025),
  casos = c(10, 20, 15),
  populacao = c(50000, 50000, 100000)
)
calcular_indicador(
  dados, "casos", "populacao", grupo = "ano", tipo = "taxa"
)
```

calcular_taxa	<i>Calculate crude epidemiological rates</i>
---------------	--

Description

Calculates ‘eventos / populacao * multiplicador’ with explicit validation of counts and denominators. Missing values propagate to the result.

Usage

```
calcular_taxa(
  eventos,
  populacao,
  multiplicador = 1e+05,
  zero_denominador = c("na", "erro")
)
```

Arguments

- eventos Non-negative event counts.
- populacao Non-negative population or person-time denominators.
- multiplicador Scale of the rate, default 100,000.
- zero_denominador How to handle zero denominators: “na” returns ‘NA’, while “erro” stops.

Value

A numeric vector with the calculated rates.

Examples

```
calcular_taxa(c(10, 25), c(10000, 20000))
calcular_taxa(25, 20000, multiplicador = 1000)
```

`calendario_epidemiologico`*Generate a Brazilian epidemiological calendar*

Description

Generate a Brazilian epidemiological calendar

Usage

```
calendario_epidemiologico(ano)
```

Arguments

`ano` One epidemiological year.

Value

A data frame with the 52 or 53 epidemiological weeks in the year.

Examples

```
calendario_epidemiologico(2026)
```

`cnes`*Query the National Registry of Health Establishments (CNES)*

Description

Supports establishments, physical resources, human resources and health teams. Use `'datasus_catalogo("cnes")'` to list the available datasets.

Usage

```
cnes(  
  conjunto = "estabelecimentos",  
  uf = NULL,  
  linha = NULL,  
  coluna = NULL,  
  conteudo = 1,  
  periodo = "last",  
  filtros = list()  
)
```

Arguments

conjunto	Dataset name listed by <code>'datasus_catalogo("sih")'</code> .
uf	Two-letter state abbreviation. <code>'NULL'</code> uses the Brazil form.
linha	Row dimension. <code>'NULL'</code> selects the form's first dimension.
coluna	Column dimension. <code>'NULL'</code> selects <code>"Não ativa"</code> .
conteudo	Measure label, raw TABNET value, or one-based index.
periodo	<code>"last"</code> for the latest competence, an exact period label or raw value, a four-digit year (all available competences in that year), or a vector of these values.
filtros	Named list of filters. Names and choices are available from <code>[datasus_opcoes()]</code> .

Value

A data frame containing the TABNET result.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  cnes(uf = "MS")
  cnes(
    conjunto = "leitos_internacao",
    uf = "MS",
    periodo = "last"
  )
})
options(old_options)
```

completar_territorios *Complete territorial and temporal combinations*

Description

Adds absent territory-period rows while protecting existing observations. By default the territorial universe is the set observed in `'dados'`. Supply `'uf'` to complete all current territories in one or more states, or `'territorios'` for an explicit universe. If `'periodos'` is omitted, the distinct periods observed in the data are used.

Usage

```
completar_territorios(
  dados,
  codigo,
  periodo = NULL,
  grupo = NULL,
  nivel = c("municipio", "uf", "regiao"),
  territorios = NULL,
  uf = NULL,
  periodos = NULL,
  preencher = list(),
  adicionar = TRUE
)
```

Arguments

<code>dados</code>	A data frame.
<code>codigo</code>	Name of the territorial code column.
<code>periodo</code>	Optional name of the period column.
<code>grupo</code>	Optional names of grouping columns whose observed combinations must be completed separately.
<code>nivel</code>	Territorial level: "municipio", "uf" or "regiao".
<code>territorios</code>	Optional vector defining the territorial universe.
<code>uf</code>	Optional state selector used to define the current territorial universe. For municipality data it includes every current municipality in the selected states.
<code>periodos</code>	Optional vector defining the period universe.
<code>preencher</code>	Named list of scalar values used only for rows created by the function, for example 'list(casos = 0)'.
<code>adicionar</code>	Whether to append current territorial attributes with [adicionar_territorio()].

Value

A data frame ordered by groups, territory and period.

Examples

```
dados <- data.frame(
  codmun = c("500270", "500270", "500370"),
  ano = c(2023, 2025, 2023),
  casos = c(10, 12, 5)
)
completar_territorios(
  dados, "codmun", "ano",
  periodos = 2023:2025,
  preencher = list(casos = 0)
)
```

datasus_catalogo	<i>List supported DATASUS datasets</i>
------------------	--

Description

Returns the local catalog used by the health-services query functions. This function does not access the network.

Usage

```
datasus_catalogo(sistema = NULL)
```

Arguments

sistema	Optional system name: "sih", "sia", "cnes", "populacao", "sinan", "pni", "siscan", "sisvan" or "financiamento", "sim" or "sinasc".
---------	--

Value

A data frame with the system, dataset name, category, description and geographic form scope.

Examples

```
datasus_catalogo()
datasus_catalogo("cnes")
```

datasus_dicionario	<i>Inspect curated DATASUS field dictionaries</i>
--------------------	---

Description

Returns the fields currently standardized by [datasus_padronizar()]. Contemporary schemas cover the variables documented in the official ESAVI, e-SUS Notifica, PNI and hospital-occupancy dictionaries. Fields added by a source after the packaged dictionary was released remain untouched and can be detected with [datasus_validar_esquema()].

Usage

```
datasus_dicionario(sistema, tipo = NULL)
```

Arguments

sistema	System: "sim", "sinasc", "sih", "esavi", "sindrome_gripal", "pni_doses" or "ocupacao_hospitalar".
tipo	Optional raw file type. 'NULL' selects the default type.

Value

A data frame with original field, standardized field, description, target class and date format.

Examples

```
datasus_dicionario("sim")
datasus_dicionario("sih", "RD")
```

datasus_opcoes	<i>Inspect the options of a DATASUS query</i>
----------------	---

Description

Reads the current TABNET form and returns its row, column, measure, period and filter choices. Filter names in the returned ‘filtros’ list are the names accepted by the query functions.

Usage

```
datasus_opcoes(sistema, conjunto = NULL, uf = NULL, abrangencia = NULL)
```

Arguments

sistema	System name accepted by [datasus_catalogo()].
conjunto	Dataset name listed by [datasus_catalogo()]. When omitted, uses the default dataset for the system.
uf	State abbreviation, two-digit IBGE code or state name. When ‘NULL’, uses the Brazil form.
abrangencia	Optional geographic detail for SIM and SINASC: “municipio” for the nation-wide municipal form or “uf” for the region/state form. Other systems retain their existing behavior.

Value

An object of class ‘datasus_opcoes’. Its components are data frames named ‘linha’, ‘coluna’, ‘conteudo’ and ‘periodo’, plus a named list ‘filtros’.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  op <- datasus_opcoes("sih", uf = "MS")
  op$conteudo
  op$filtros$carater_atendimento
```

```
  })  
  options(old_options)
```

datasus_padronizar	<i>Standardize common fields in DATASUS microdata</i>
--------------------	---

Description

Renames curated fields and converts documented dates, identifiers, numeric measures and logical indicators. Unrecognized columns and coded category values are preserved exactly as published.

Usage

```
datasus_padronizar(dados, sistema, tipo = NULL)
```

Arguments

<code>dados</code>	A data frame containing raw DATASUS records.
<code>sistema</code>	System accepted by [datasus_dicionario()].
<code>tipo</code>	Optional raw file type. 'NULL' selects the default type.

Value

The input data frame with curated fields renamed and typed. Provenance is preserved and the applied dictionary is attached as attribute "datasus_dicionario".

Examples

```
example <- data.frame(  
  MUNIC_RES = "120040",  
  DT_INTER = "20240110",  
  DIAG_PRINC = "J18"  
)  
datasus_padronizar(example, "sih")
```

`datasus_proveniencia` *Retrieve DATASUS provenance metadata*

Description

Retrieve DATASUS provenance metadata

Usage

```
datasus_proveniencia(x)
```

Arguments

`x` An object returned by `[opendatasus_catalogo()]`, `[opendatasus_recurso()]`, `[opendatasus_baixar()]` or `[opendatasus_ler()]`.

Value

A named list, or 'NULL' when no provenance metadata is attached.

`datasus_territorios` *List Brazilian territories*

Description

Returns the package's offline territorial reference. The municipality table is generated from the official IBGE Localities API and contains current municipality, state, macroregion, immediate/intermediate region and legacy micro/mesoregion codes and names.

Usage

```
datasus_territorios(nivel = c("municipio", "uf", "regiao"), uf = NULL)
```

Arguments

`nivel` Territorial level: "municipio", "uf" or "regiao".
`uf` Optional state selector. It accepts a two-digit IBGE code, state abbreviation or full state name. It is available for municipality and state results.

Value

A data frame. Source and extraction metadata are available through `[datasus_proveniencia()]`.

Examples

```
datasus_territorios("regiao")
datasus_territorios("uf")
head(datasus_territorios("municipio", uf = "MS"))
```

`datasus_validar_esquema`*Validate curated DATASUS schemas*

Description

Compares the columns of a raw or standardized data frame with fields in [datasus_dicionario()]. This detects missing fields and incompatible target classes without treating newly introduced source columns as errors.

Usage

```
datasus_validar_esquema(  
  dados,  
  sistema,  
  tipo = NULL,  
  campos = NULL,  
  estrito = FALSE  
)
```

Arguments

<code>dados</code>	A data frame containing raw or standardized records.
<code>sistema</code>	System accepted by [datasus_dicionario()].
<code>tipo</code>	Optional raw file type for SIM, SINASC or SIH.
<code>campos</code>	Optional source or standardized field names to require. 'NULL' checks every curated field for the selected system.
<code>estrito</code>	Whether missing or incompatibly typed standardized fields should raise an error.

Value

A data frame with source and standardized field names, presence, observed column and class, expected class and status. Attribute "campos_extras" lists columns outside the curated dictionary.

Examples

```
dados <- data.frame(  
  dt_vacina = "2025-01-10",  
  co_municipio_paciente = "5002704"  
)  
datasus_validar_esquema(dados, "pni_doses")
```

esavi

*Read anonymous ESAVI notifications***Description**

Downloads anonymous individual records from the e-SUS Notifica ESAVI module. The source contains notifications since January 2021 and is continuously updated. An event following immunization does not by itself establish a causal association with a vaccine.

Usage

```
esavi(
  formato = "CSV",
  destino = NULL,
  cache = TRUE,
  atualizar = FALSE,
  n_max = Inf,
  colunas = NULL,
  normalizar = FALSE,
  ...
)
```

Arguments

formato	File format, "CSV" or "JSON".
destino	Optional destination file or existing directory.
cache	Whether to reuse the local OpenDataSUS cache.
atualizar	Whether to force a fresh metadata query and download.
n_max	Maximum number of rows to read.
colunas	Optional character vector selecting columns during CSV parsing.
normalizar	Whether to apply the curated contemporary schema with [datasus_padronizar()].
...	Additional arguments passed to the underlying reader.

Value

The parsed OpenDataSUS resource with provenance metadata.

References

OpenDataSUS. ESAVI - Dados sobre Eventos Supostamente Atribuíveis a Vacinação. <https://dadosabertos.saude.gov.br/dataset/esavi>

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  eventos <- esavi(n_max = 1000)
  datasus_proveniencia(eventos)
})
options(old_options)
```

esus_sindrome_gripal *Read e-SUS Notifica mild influenza-like illness records*

Description

Downloads anonymous mild and moderate influenza-like illness notifications published by annual dataset and state. These records are distinct from hospitalized severe acute respiratory syndrome records returned by [sivep_gripe()].

Usage

```
esus_sindrome_gripal(
  uf,
  ano = "last",
  formato = "CSV",
  destino = NULL,
  cache = TRUE,
  atualizar = FALSE,
  n_max = Inf,
  colunas = NULL,
  normalizar = FALSE,
  ...
)
```

Arguments

uf	One Brazilian state abbreviation, IBGE code or state name.
ano	Dataset year from 2020 onwards, or "last" for the latest annual dataset currently published.
formato	File format. The annual state resources are published as "CSV".
destino	Optional destination file or existing directory.
cache	Whether to reuse the local OpenDataSUS cache.
atualizar	Whether to force a fresh metadata query and download.

n_max	Maximum number of rows to read.
colunas	Optional character vector selecting columns during CSV parsing.
normalizar	Whether to apply the curated contemporary schema with [datasus_padronizar()].
...	Additional arguments passed to the underlying reader.

Value

The parsed OpenDataSUS resource with provenance metadata.

References

OpenDataSUS. Notificações de Síndrome Gripal. <https://dadosabertos.saude.gov.br/dataset?query=sindrome+gripal>

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  casos <- esus_sindrome_gripal(uf = "MS", ano = 2024, n_max = 1000)
})
options(old_options)
```

extrair_codigo_ibge	<i>Extract IBGE codes from DATASUS labels</i>
---------------------	---

Description

Extracts the first territorial code embedded in labels such as "500270 Campo Grande" and then validates and converts it with [normalizar_codigo_ibge()].

Usage

```
extrair_codigo_ibge(
  x,
  nivel = c("municipio", "uf", "regiao"),
  formato = NULL,
  desconhecido = c("erro", "na", "manter")
)
```

Arguments

x	Character vector containing codes or labeled values.
nivel	Territorial level: "municipio", "uf" or "regiao".
formato	Output format. Municipalities support "ibge" (seven digits) and "datasus" (six digits). States and regions additionally support "sigla" and "nome".
desconhecido	How to handle unknown values: "erro", "na" or "manter".

Value

A normalized character vector.

Examples

```
extrair_codigo_ibge(c("500270 Campo Grande", "500370 Dourados"))
```

financiamento_sus	<i>Query legacy SUS financing tables</i>
-------------------	--

Description

Provides the three financial tables linked by the DATASUS TABNET catalog: federal resources, approved production values by provider, and payment authorization guides. Availability periods vary and may be historical.

Usage

```
financiamento_sus(
  conjunto = "recursos_federais",
  uf = NULL,
  linha = NULL,
  coluna = NULL,
  conteudo = 1,
  periodo = "last",
  filtros = list()
)
```

Arguments

conjunto	Dataset name listed by 'datasus_catalogo("sih)".
uf	Two-letter state abbreviation. 'NULL' uses the Brazil form.
linha	Row dimension. 'NULL' selects the form's first dimension.
coluna	Column dimension. 'NULL' selects "Não ativa".
conteudo	Measure label, raw TABNET value, or one-based index.
periodo	"last" for the latest competence, an exact period label or raw value, a four-digit year (all available competences in that year), or a vector of these values.
filtros	Named list of filters. Names and choices are available from [datasus_opcoes()].

Value

A data frame containing the TABNET result.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  financiamento_sus(uf = "MS")
  financiamento_sus(conjunto = "producao_prestador", uf = "MS")
})
options(old_options)
```

intervalo_taxa

Calculate exact Poisson confidence intervals for rates

Description

Uses chi-squared quantiles for exact Poisson count limits and divides them by the supplied denominator. Event counts must be whole numbers.

Usage

```
intervalo_taxa(
  eventos,
  populacao,
  multiplicador = 1e+05,
  confianca = 0.95,
  zero_denominador = c("na", "erro")
)
```

Arguments

eventos	Non-negative event counts.
populacao	Non-negative population or person-time denominators.
multiplicador	Scale of the rate, default 100,000.
confianca	Confidence level between 0 and 1.
zero_denominador	How to handle zero denominators: "na" returns 'NA', while "erro" stops.

Value

A data frame with event counts, denominators, rates and lower and upper confidence limits.

Examples

```
intervalo_taxa(c(0, 10), c(10000, 10000))
```

juntar_populacao	<i>Join validated population denominators</i>
------------------	---

Description

Performs a many-to-one join from observations to a population table, preserving observation order and rejecting ambiguous denominator keys. This is designed to connect outputs from [populacao_residente()] to event tables before calculating population-based indicators.

Usage

```
juntar_populacao(
  dados,
  populacao,
  por,
  coluna_populacao = "populacao",
  nome = "populacao",
  ausente = c("erro", "na"),
  sobrescrever = FALSE
)
```

Arguments

<code>dados</code>	Observation data frame.
<code>populacao</code>	Population data frame.
<code>por</code>	Character vector of join columns. An unnamed vector uses the same names in both tables. In a named vector, names refer to columns in ‘dados’ and values to columns in ‘populacao’.
<code>coluna_populacao</code>	Name of the numeric denominator column in ‘populacao’.
<code>nome</code>	Name assigned to the joined denominator column.
<code>ausente</code>	How to handle observations without a denominator: “erro” stops and “na” keeps them with a missing value.
<code>sobrescrever</code>	Whether an existing ‘nome’ column in ‘dados’ may be replaced.

Value

‘dados’ with one validated population denominator column appended.

Examples

```
eventos <- data.frame(codigo = c("A", "B"), ano = 2024, casos = c(2, 4))
denominadores <- data.frame(
  municipio = c("A", "B"), ano = 2024, habitantes = c(1000, 2000)
)
juntar_populacao(
  eventos, denominadores,
  por = c(codigo = "municipio", ano = "ano"),
  coluna_populacao = "habitantes"
)
```

letalidade	<i>Calculate grouped case fatality</i>
------------	--

Description

Calculate grouped case fatality

Usage

```
letalidade(
  dados,
  obitos,
  casos,
  grupo = NULL,
  multiplicador = 100,
  confianca = NULL,
  na_rm = FALSE,
  zero_denominador = c("na", "erro")
)
```

Arguments

<code>dados</code>	A non-empty data frame.
<code>obitos</code>	Name of the deaths among cases column.
<code>casos</code>	Name of the cases column.
<code>grupo</code>	Optional character vector naming grouping columns.
<code>multiplicador</code>	Positive scale, default 100 for a percentage.
<code>confianca</code>	Optional confidence level. Exact intervals are available for rates, proportions and case fatality, but not for ratios.
<code>na_rm</code>	Whether rows with a missing numerator or denominator should be removed pairwise within each group. A group containing no complete row remains missing.
<code>zero_denominador</code>	How to handle zero denominators: "na" returns 'NA', while "erro" stops.

Value

A data frame with aggregated counts and ‘letalidade’.

Examples

```
dados <- data.frame(doenca = c("A", "A"), obitos = c(1, 2),
                    casos = c(20, 30))
letalidade(dados, "obitos", "casos", grupo = "doenca")
```

media_movel	<i>Calculate moving averages</i>
-------------	----------------------------------

Description

Calculate moving averages

Usage

```
media_movel(
  x,
  janela = 7L,
  alinhamento = c("direita", "centro", "esquerda"),
  parcial = FALSE,
  na_rm = FALSE
)
```

Arguments

x	Numeric vector.
janela	Positive window size.
alinhamento	Window alignment: “direita”, “centro” or “esquerda”.
parcial	Whether edge windows may contain fewer than ‘janela’ observations.
na_rm	Whether missing values should be removed within each window.

Value

A numeric vector of the same length as ‘x’.

Examples

```
media_movel(1:7, janela = 3)
media_movel(c(1, NA, 3, 4), janela = 2, na_rm = TRUE)
```

microdados_arquivos *Discover raw DATASUS microdata files*

Description

Builds the official DATASUS transfer paths and optionally checks whether each file currently exists. SIM and SINASC files are annual; SIH files are monthly.

Usage

```
microdados_arquivos(
  sistema,
  tipo = NULL,
  ano,
  mes = NULL,
  uf = NULL,
  preliminares = TRUE,
  verificar = TRUE,
  timeout = 120
)
```

Arguments

sistema	System: "sim", "sinasc" or "sih".
tipo	File type returned by [microdados_catalago()]. 'NULL' selects the default type for the system.
ano	One or more four-digit years.
mes	One or more months from 1 to 12. Required for SIH.
uf	One or more state abbreviations, two-digit IBGE codes or state names. Required for UF-scoped types.
preliminares	Whether preliminary directories may be considered.
verificar	Whether to verify file existence on the DATASUS server.
timeout	Network timeout in seconds for file discovery.

Value

A data frame containing official file names, URLs and existence checks. Provenance records the selection and consultation time.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
```

```
try({
  microdados_arquivos("sim", ano = 2023, uf = "RR")
  microdados_arquivos("sih", ano = 2024, mes = 1, uf = "AC")
})
options(old_options)
```

microdados_baixar	<i>Download raw DATASUS DBC files</i>
-------------------	---------------------------------------

Description

Discovers and downloads one or more official DBC files. Downloads use a dedicated cache below option 'datasus.cache_dir'; 'atualizar = TRUE' requests a fresh copy.

Usage

```
microdados_baixar(
  sistema,
  tipo = NULL,
  ano,
  mes = NULL,
  uf = NULL,
  destino = NULL,
  cache = TRUE,
  atualizar = FALSE,
  preliminares = TRUE,
  verificar = TRUE,
  timeout = 240
)
```

Arguments

sistema	System: "sim", "sinasc" or "sih".
tipo	File type returned by [microdados_catalogo()]. 'NULL' selects the default type for the system.
ano	One or more four-digit years.
mes	One or more months from 1 to 12. Required for SIH.
uf	One or more state abbreviations, two-digit IBGE codes or state names. Required for UF-scoped types.
destino	Optional destination directory. 'NULL' uses the package cache, or a session temporary directory when 'cache = FALSE'.
cache	Whether to reuse the disk cache.
atualizar	Whether to request a fresh copy of already cached files.
preliminares	Whether preliminary directories may be considered.
verificar	Whether to verify file existence on the DATASUS server.
timeout	Network timeout in seconds for file discovery.

Value

A data frame describing the local files. Use [datasus_proveniencia()] for URLs and checksums.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  files <- microdados_baixar("sih", ano = 2024, mes = 1, uf = "AC")
  datasus_proveniencia(files)
})
options(old_options)
```

microdados_catalogo	<i>List supported DATASUS microdata files</i>
---------------------	---

Description

Returns the local catalog of raw DBC/DBF file families supported by the package. These files provide record-level data, unlike aggregated TABNET results.

Usage

```
microdados_catalogo(sistema = NULL)
```

Arguments

sistema Optional system: "sim", "sinasc" or "sih".

Value

A data frame with system, upstream source, file type, description, geographic scope and frequency.

Examples

```
microdados_catalogo()
microdados_catalogo("sih")
```

microdados_1er

*Download and read raw DATASUS microdata***Description**

Downloads the requested DBC files and reads them directly in memory using the native ‘datasusr’ decoder. Column selection and ‘n_max’ are applied during parsing, which is useful for large SIH files.

Usage

```
microdados_1er(
  sistema,
  tipo = NULL,
  ano,
  mes = NULL,
  uf = NULL,
  destino = NULL,
  cache = TRUE,
  atualizar = FALSE,
  preliminares = TRUE,
  verificar = TRUE,
  timeout = 240,
  colunas = NULL,
  n_max = Inf,
  normalizar = FALSE,
  juntar = TRUE,
  ...
)
```

Arguments

sistema	System: “sim”, “sinasc” or “sih”.
tipo	File type returned by [microdados_catalogo()]. ‘NULL’ selects the default type for the system.
ano	One or more four-digit years.
mes	One or more months from 1 to 12. Required for SIH.
uf	One or more state abbreviations, two-digit IBGE codes or state names. Required for UF-scoped types.
destino	Optional destination directory. ‘NULL’ uses the package cache, or a session temporary directory when ‘cache = FALSE’.
cache	Whether to reuse the disk cache.
atualizar	Whether to request a fresh copy of already cached files.
preliminares	Whether preliminary directories may be considered.

<code>verificar</code>	Whether to verify file existence on the DATASUS server.
<code>timeout</code>	Network timeout in seconds for file discovery.
<code>colunas</code>	Optional vector of original or lower-case columns to read.
<code>n_max</code>	Maximum number of records to read from each file.
<code>normalizar</code>	Whether to rename and type common fields with <code>[datasus_padronizar()]</code> .
<code>juntar</code>	Whether to combine multiple files. If <code>'FALSE'</code> , returns a named list.
<code>...</code>	Additional arguments passed to <code>[datasusr::read_datasus_dbc()]</code> .

Value

A data frame, or a named list when `'juntar = FALSE'`, with provenance metadata attached.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  admissions <- microdados_ler(
    "sih",
    ano = 2024,
    mes = 1,
    uf = "AC",
    colunas = c("MUNIC_RES", "DT_INTER", "DIAG_PRINC", "VAL_TOT"),
    n_max = 1000,
    normalizar = TRUE
  )
})
options(old_options)
```

`normalizar_codigo_ibge`

Normalize IBGE territorial codes

Description

Validates current territorial identifiers against the bundled IBGE reference. Municipality inputs may use the full seven-digit IBGE code or the six-digit form commonly returned by DATASUS. State and region inputs may also use abbreviations or full names.

Usage

```
normalizar_codigo_ibge(
  codigo,
  nivel = c("municipio", "uf", "regiao"),
  formato = NULL,
  desconhecido = c("erro", "na", "manter")
)
```

Arguments

codigo	Vector of territorial identifiers.
nivel	Territorial level: "municipio", "uf" or "regiao".
formato	Output format. Municipalities support "ibge" (seven digits) and "datasus" (six digits). States and regions additionally support "sigla" and "nome".
desconhecido	How to handle unknown values: "erro", "na" or "manter".

Value

A character vector with the same length as 'codigo'.

Examples

```
normalizar_codigo_ibge(c("500270", "5003702"))
normalizar_codigo_ibge(c("MS", "Mato Grosso do Sul"), "uf", "ibge")
```

ocupacao_hospitalar *Read COVID-19 hospital occupancy records*

Description

Downloads annual records from the e-SUS Notifica Hospital Admissions module. The published files cover SUS clinical and intensive-care beds allocated to suspected or confirmed COVID-19 cases. Fields added in 2022 are not populated in earlier records.

Usage

```
ocupacao_hospitalar(
  ano = "last",
  formato = "CSV",
  destino = NULL,
  cache = TRUE,
  atualizar = FALSE,
  n_max = Inf,
  colunas = NULL,
  normalizar = FALSE,
  ...
)
```

Arguments

<code>ano</code>	Resource year or "last" for the latest year currently published.
<code>formato</code>	File format, "CSV" or "JSON".
<code>destino</code>	Optional destination file or existing directory.
<code>cache</code>	Whether to reuse the local OpenDataSUS cache.
<code>atualizar</code>	Whether to force a fresh metadata query and download.
<code>n_max</code>	Maximum number of rows to read.
<code>colunas</code>	Optional character vector selecting columns during CSV parsing.
<code>normalizar</code>	Whether to apply the curated contemporary schema with <code>[datasus_padronizar()]</code> .
<code>...</code>	Additional arguments passed to the underlying reader.

Value

The parsed OpenDataSUS resource with provenance metadata.

References

OpenDataSUS. Registro de Ocupação Hospitalar COVID-19. <https://dadosabertos.saude.gov.br/dataset/registro-de-ocupacao-hospitalar-covid-19>

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  leitos <- ocupacao_hospitalar(ano = 2022, n_max = 1000)
})
options(old_options)
```

`opendatasus_arquivos` *Expand downloadable files from OpenDataSUS resources*

Description

Some OpenDataSUS resources, notably state-level influenza-like illness datasets, publish several file parts as links inside the resource description instead of the primary URL field. This function expands both representations to one row per downloadable file.

Usage

```
opendatasus_arquivos(
  conjunto,
  recurso = NULL,
  formato = NULL,
  cache = TRUE,
  atualizar = FALSE
)
```

Arguments

conjunto	Dataset slug returned by [opendatasus_catalogo()].
recurso	Optional exact resource name or identifier.
formato	Optional resource format.
cache	Whether to cache portal metadata for the duration controlled by option 'datasus.cache_ttl'.
atualizar	Whether to ignore cached metadata and query the portal again.

Value

A data frame with one row per downloadable file and its parent resource identifier, part number and URL.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  opendatasus_arquivos(
    "notificacoes-de-sindrome-gripal-leve-2024",
    recurso = "Dados MS - 20/12",
    formato = "CSV"
  )
})
options(old_options)
```

opendatasus_baixar	<i>Download a resource from OpenDataSUS</i>
--------------------	---

Description

Resolves a resource from the live portal metadata, downloads it atomically and records its origin and MD5 checksum. By default, files are reused from the package cache. A cached file is refreshed automatically when the resource update timestamp changes.

Usage

```
opendatasus_baixar(
  conjunto,
  recurso = NULL,
  ano = "last",
  formato = NULL,
  destino = NULL,
  cache = TRUE,
  atualizar = FALSE
)
```

Arguments

conjunto	Dataset slug returned by [opendatasus_catalogo()].
recurso	Optional exact resource name or stable resource identifier.
ano	Resource year, "last" for the latest dated resource, or 'NULL'. Ignored when 'recurso' is supplied.
formato	Resource format. When both 'recurso' and 'formato' are 'NULL', CSV is preferred.
destino	Optional destination file or existing directory. 'NULL' uses the package cache, or a temporary file when 'cache = FALSE'.
cache	Whether to cache portal metadata for the duration controlled by option 'datasus.cache_ttl'.
atualizar	Whether to ignore cached metadata and query the portal again.

Value

The normalized local file path, with classes "datasus_arquivo" and "character". Use [datasus_proveniencia()] to inspect its origin.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  file <- opendatasus_baixar(
    "arboviroses-dengue",
    ano = 2025,
    formato = "CSV"
  )
  datasus_proveniencia(file)
})
options(old_options)
```

opendatasus_catalogo *Search the OpenDataSUS catalog*

Description

Searches the current OpenDataSUS portal and returns lightweight metadata for matching datasets. Use [opendatasus_recurso()] to inspect the files and API links published for one dataset.

Usage

```
opendatasus_catalogo(  
  busca = NULL,  
  grupo = NULL,  
  formato = NULL,  
  pagina = 1L,  
  limite = 20L,  
  cache = TRUE,  
  actualizar = FALSE  
)
```

Arguments

busca	Optional free-text search.
grupo	Optional OpenDataSUS group slug.
formato	Optional resource format, such as "CSV", "JSON" or "PDF".
pagina	Positive page number.
limite	Number of results requested per page.
cache	Whether to cache portal metadata for the duration controlled by option 'datasus.cache_ttl'.
actualizar	Whether to ignore cached metadata and query the portal again.

Value

A data frame with dataset names, titles, descriptions, formats and groups. Attribute "datasus_proveniencia" records the source and consultation time.

Examples

```
old_options <- options(  
  datasus.timeout = 5,  
  datasus.download_timeout = 15,  
  datasus.max_tries = 1  
)  
try({  
  opendatasus_catalogo("dengue")  
  opendatasus_catalogo(grupo = "arboviroses", formato = "CSV")  
})
```

```
  })
  options(old_options)
```

opendatasus_1er

Download and read tabular OpenDataSUS data

Description

Selects and downloads one CSV or JSON resource, then reads it into R. CSV delimiters are detected automatically. For very large datasets, use ‘n_max’ while exploring the columns, or call [opendatasus_baixar()] and use a streaming database engine.

Usage

```
opendatasus_1er(
  conjunto,
  recurso = NULL,
  ano = "last",
  formato = NULL,
  destino = NULL,
  cache = TRUE,
  atualizar = FALSE,
  n_max = Inf,
  colunas = NULL,
  ...
)
```

Arguments

conjunto	Dataset slug returned by [opendatasus_catalogo()].
recurso	Optional exact resource name or stable resource identifier.
ano	Resource year, “last” for the latest dated resource, or ‘NULL’. Ignored when ‘recurso’ is supplied.
formato	Resource format. When both ‘recurso’ and ‘formato’ are ‘NULL’, CSV is preferred.
destino	Optional destination file or existing directory. ‘NULL’ uses the package cache, or a temporary file when ‘cache = FALSE’.
cache	Whether to cache portal metadata for the duration controlled by option ‘data-sus.cache_ttl’.
atualizar	Whether to ignore cached metadata and query the portal again.
n_max	Maximum number of CSV rows to read. For JSON data, the limit is applied after parsing when the result is a data frame.
colunas	Optional character vector selecting columns while CSV files are parsed. JSON columns are selected after parsing.
...	Additional arguments passed to [readr::read_delim()] or [jsonlite::fromJSON()].

Value

The parsed resource. Attribute “datasus_proveniencia” records the selected resource, download time, local file and checksum.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  dengue <- opendatasus_ler(
    "arboviroses-dengue",
    ano = 2025,
    formato = "CSV",
    n_max = 1000
  )
  datasus_proveniencia(dengue)
})
options(old_options)
```

opendatasus_processor *Process large OpenDataSUS CSV resources in chunks*

Description

Downloads the selected resource using the regular atomic cache, expands multipart resources, and invokes a callback for bounded-size chunks. Returning small summaries or ‘NULL’ from the callback keeps memory use independent of the complete dataset size.

Usage

```
opendatasus_processor(
  conjunto,
  FUN,
  recurso = NULL,
  ano = "last",
  formato = "CSV",
  destino = NULL,
  cache = TRUE,
  atualizar = FALSE,
  colunas = NULL,
  tamanho_bloco = 100000L,
  sistema = NULL,
  ...
)
```

Arguments

conjunto	Dataset slug returned by [opendatasus_catalogo()].
FUN	Function called as 'FUN(dados, posicao, arquivo)', where 'posicao' is the first row position within a file and 'arquivo' is the one-based file-part index.
recurso	Optional exact resource name or stable resource identifier.
ano	Resource year, "last" for the latest dated resource, or 'NULL'. Ignored when 'recurso' is supplied.
formato	Resource format. When both 'recurso' and 'formato' are 'NULL', CSV is preferred.
destino	Optional destination file or existing directory. 'NULL' uses the package cache, or a temporary file when 'cache = FALSE'.
cache	Whether to cache portal metadata for the duration controlled by option 'datasus.cache_ttl'.
atualizar	Whether to ignore cached metadata and query the portal again.
colunas	Optional character vector selecting columns while CSV files are parsed. JSON columns are selected after parsing.
tamanho_bloco	Positive number of rows parsed per chunk.
sistema	Optional dictionary system accepted by [datasus_padronizar()]. When supplied, each chunk is standardized before 'FUN' is called.
...	Additional arguments passed to [readr::read_delim()] or [jsonlite::fromJSON()].

Value

An object of class "datasus_processamento" containing callback results, row, chunk and file counts, and provenance for every file.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  summary <- opendatasus_processor(
    "doses-aplicadas-pelo-programa-de-nacional-de-imunizacoes-pni-2026",
    recurso = "Vacinação - Julho 2026",
    ano = NULL,
    formato = "CSV",
    FUN = function(dados, posicao, arquivo) nrow(dados),
    tamanho_bloco = 50000
  )
})
options(old_options)
```

opendatasus_recurcos *List resources from an OpenDataSUS dataset*

Description

List resources from an OpenDataSUS dataset

Usage

```
opendatasus_recurcos(conjunto, cache = TRUE, atualizar = FALSE)
```

Arguments

conjunto	Dataset slug returned by [opendatasus_catalogo()].
cache	Whether to cache portal metadata for the duration controlled by option 'datasus.cache_ttl'.
atualizar	Whether to ignore cached metadata and query the portal again.

Value

A data frame with one row per published resource, including its stable identifier, name, format, inferred year, URL and update date.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  opendatasus_recurcos("srag-2019-a-2026")
  opendatasus_recurcos("arboviroses-dengue")
})
options(old_options)
```

padronizar_idade *Directly standardize rates by age*

Description

Calculates a weighted average of age-specific rates using a supplied standard population. Independent Poisson counts are assumed for the standard error. Optional confidence limits use a normal approximation.

Usage

```
padronizar_idade(
  eventos,
  populacao,
  idade,
  populacao_padrao,
  grupo = NULL,
  multiplicador = 1e+05,
  confianca = NULL,
  na_rm = FALSE
)
```

Arguments

<code>eventos</code>	Non-negative event counts by age stratum.
<code>populacao</code>	Positive population or person-time by age stratum.
<code>idade</code>	Age-stratum labels.
<code>populacao_padrao</code>	Standard population weights. Supply either one value per input row or a named vector whose names match ‘idade’.
<code>grupo</code>	Optional analysis group, such as year or municipality. Each age stratum must occur at most once within a group.
<code>multiplicador</code>	Scale of the standardized rate, default 100,000.
<code>confianca</code>	Optional confidence level. ‘NULL’ omits confidence limits.
<code>na_rm</code>	Whether incomplete age strata should be removed and the remaining standard weights renormalized.

Value

A data frame with standardized rate, standard error, confidence limits, number of strata and proportion of standard weight represented.

References

Ahmad OB et al. (2001). Age standardization of rates: a new WHO standard. World Health Organization.

Examples

```
padronizar_idade(
  eventos = c(10, 40),
  populacao = c(1000, 1000),
  idade = c("0-49", "50+"),
  populacao_padrao = c("0-49" = 800, "50+" = 200)
)
```

pni_doses

*Read individual PNI dose records***Description**

Downloads anonymous vaccination records published in monthly files by the National Immunization Program. This record-level source complements the aggregated historical TABNET series returned by [pni_imunizacoes()].

Usage

```
pni_doses(
  ano = "last",
  mes = "last",
  formato = "CSV",
  destino = NULL,
  cache = TRUE,
  atualizar = FALSE,
  n_max = Inf,
  colunas = NULL,
  normalizar = FALSE,
  ...
)
```

Arguments

ano	Dataset year from 2020 onwards, or "last" for the most recent annual dataset currently published.
mes	Month number, Portuguese month name, or "last" for the latest month currently published in the selected year and format.
formato	File format, "CSV" or "JSON".
destino	Optional destination file or existing directory.
cache	Whether to reuse the local OpenDataSUS cache.
atualizar	Whether to force a fresh metadata query and download.
n_max	Maximum number of rows to read.
colunas	Optional character vector selecting columns during CSV parsing.
normalizar	Whether to apply the curated contemporary schema with [datasus_padronizar()].
...	Additional arguments passed to the underlying reader.

Value

The parsed OpenDataSUS resource with provenance metadata.

References

OpenDataSUS. Doses aplicadas pelo Programa Nacional de Imunizações. <https://dadosabertos.saude.gov.br/dataset?query=doses+aplicadas+PNI>

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  doses <- pni_doses(ano = 2025, mes = 1, n_max = 1000)
})
options(old_options)
```

pni_imunizacoes

Query legacy immunization data from PNI

Description

Provides applied doses and vaccination coverage from the legacy TABNET series, whose latest available year is currently 2022. DATASUS reports that coverage and applied-dose data are under review for integration inconsistencies.

Usage

```
pni_imunizacoes(
  conjunto = "doses_aplicadas",
  uf = NULL,
  linha = NULL,
  coluna = NULL,
  conteudo = 1,
  periodo = "last",
  filtros = list()
)
```

Arguments

conjunto	Dataset name listed by 'datasus_catalogo("sih)".
uf	Two-letter state abbreviation. 'NULL' uses the Brazil form.
linha	Row dimension. 'NULL' selects the form's first dimension.
coluna	Column dimension. 'NULL' selects "'Não ativa"'.
conteudo	Measure label, raw TABNET value, or one-based index.
periodo	"last" for the latest competence, an exact period label or raw value, a four-digit year (all available competences in that year), or a vector of these values.
filtros	Named list of filters. Names and choices are available from [datasus_opcoes()].

Value

A data frame containing the TABNET result.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  pni_imunizacoes(uf = "MS")
  pni_imunizacoes(
    conjunto = "cobertura",
    uf = "MS",
    periodo = 2022
  )
})
options(old_options)
```

populacao_padrao

Retrieve ready-made standard populations

Description

Returns age-group weights for the WHO 2000–2025 world standard, Segi’s world standard or the Scandinavian standard. By default weights are normalized to sum to one and can be passed directly to [padronizar_idade()].

Usage

```
populacao_padrao(
  nome = "oms_2000_2025",
  formato = c("vetor", "dados"),
  normalizar = TRUE
)
```

Arguments

nome	Standard population: “oms_2000_2025”, “segi” or “escandinava”. “oms” and “who” are accepted aliases.
formato	Output as a named numeric “vetor” or a data frame (“dados”).
normalizar	Whether weights should be normalized to sum to one.

Value

A named numeric vector or a data frame with ‘faixa_etaria’, ‘peso_publicado’ and ‘peso’.

References

Ahmad OB et al. (2001). Age standardization of rates: a new WHO standard. https://cdn.who.int/media/docs/default-source/gho-documents/global-health-estimates/gpe_discussion_paper_series_paper31_2001_age_standardization_rates.pdf

Examples

```
populacao_padrao("oms")
populacao_padrao("segi", formato = "dados")
```

populacao_residente	<i>Query resident population estimates</i>
---------------------	--

Description

Provides census, projection, retroprojection and municipal estimate datasets published in the DATA-SUS population section. The default dataset contains municipal estimates by sex and age from 2000 through 2021.

Usage

```
populacao_residente(
  conjunto = "estimativa_municipal",
  uf = NULL,
  linha = NULL,
  coluna = NULL,
  conteudo = 1,
  periodo = "last",
  filtros = list()
)
```

Arguments

conjunto	Dataset name listed by ‘datasus_catalogo("sih")’.
uf	Two-letter state abbreviation. ‘NULL’ uses the Brazil form.
linha	Row dimension. ‘NULL’ selects the form’s first dimension.
coluna	Column dimension. ‘NULL’ selects “Não ativa”.
conteudo	Measure label, raw TABNET value, or one-based index.
periodo	“last” for the latest competence, an exact period label or raw value, a four-digit year (all available competences in that year), or a vector of these values.
filtros	Named list of filters. Names and choices are available from [datasus_opcoes()].

Value

A data frame containing the TABNET result.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  populacao_residente(uf = "MS", periodo = 2021)
  populacao_residente(
    linha = "Unidade da Federação",
    periodo = c(2020, 2021)
  )
})
options(old_options)
```

proporcao	<i>Calculate grouped proportions</i>
-----------	--------------------------------------

Description

Calculate grouped proportions

Usage

```
proporcao(
  dados,
  parte,
  total,
  grupo = NULL,
  multiplicador = 100,
  confianca = NULL,
  na_rm = FALSE,
  zero_denominador = c("na", "erro")
)
```

Arguments

<code>dados</code>	A non-empty data frame.
<code>parte</code>	Name of the subset count column.
<code>total</code>	Name of the total count column.
<code>grupo</code>	Optional character vector naming grouping columns.
<code>multiplicador</code>	Positive scale, default 100 for a percentage.
<code>confianca</code>	Optional confidence level. Exact intervals are available for rates, proportions and case fatality, but not for ratios.

`na_rm` Whether rows with a missing numerator or denominator should be removed pairwise within each group. A group containing no complete row remains missing.

`zero_denominator` How to handle zero denominators: `"na"` returns `'NA'`, while `"erro"` stops.

Value

A data frame with aggregated counts and `'proporcao'`.

Examples

```
dados <- data.frame(ano = c(2024, 2024), vacinados = c(40, 45),
                    elegiveis = c(50, 50))
proporcao(dados, "vacinados", "elegiveis", grupo = "ano")
```

`semana_epidemiologica` *Convert dates to Brazilian epidemiological weeks*

Description

Epidemiological weeks run from Sunday through Saturday. Week 1 is the Sunday-to-Saturday week containing at least four days of the new year. Dates near New Year can therefore belong to the previous or following epidemiological year.

Usage

```
semana_epidemiologica(data)
```

Arguments

`data` A `'Date'`, date-time, or vector of ISO `"YYYY-MM-DD"` strings.

Value

A data frame containing the original date, epidemiological year and week, week start and end, and a stable `"YYYY-Www"` code.

References

Brazilian Ministry of Health, SINAN Epidemiological Calendar: <https://portalsinan.saude.gov.br/calendario-epidemiologico>

Examples

```
semana_epidemiologica(as.Date(c("2025-01-01", "2026-01-01")))
```

sia_producao

*Query ambulatory production from SIA/SUS***Description**

Query ambulatory production from SIA/SUS

Usage

```
sia_producao(
  conjunto = "atendimento",
  uf = NULL,
  linha = NULL,
  coluna = NULL,
  conteudo = 1,
  periodo = "last",
  filtros = list()
)
```

Arguments

conjunto	Dataset name listed by ‘datasus_catalogo("sih")’.
uf	Two-letter state abbreviation. ‘NULL’ uses the Brazil form.
linha	Row dimension. ‘NULL’ selects the form’s first dimension.
coluna	Column dimension. ‘NULL’ selects “Não ativa”.
conteudo	Measure label, raw TABNET value, or one-based index.
periodo	“last” for the latest competence, an exact period label or raw value, a four-digit year (all available competences in that year), or a vector of these values.
filtros	Named list of filters. Names and choices are available from [datasus_opcoes()].

Value

A data frame containing the TABNET result.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  sia_producao(uf = "MS")
  sia_producao(
    linha = "UF",
    conteudo = "Qtd.aprovada",
```

```
    periodo = "last"
  )
})
options(old_options)
```

sih_microdados	<i>Read SIH hospitalization microdata</i>
----------------	---

Description

Read SIH hospitalization microdata

Usage

```
sih_microdados(ano, mes, uf, tipo = "RD", ...)
```

Arguments

- ano One or more years.
- mes One or more months.
- uf One or more state abbreviations.
- tipo SIH file type, default "RD".
- ... Additional arguments passed to [microdados_ler()].

Value

Record-level SIH data.

sih_morbidade	<i>Query hospital morbidity from SIH/SUS</i>
---------------	--

Description

Provides general morbidity and external-causes views by place of hospitalization or residence. Use 'datasus_catalago("sih")' and select rows whose category is "morbidade hospitalar" to list the datasets.

Usage

```
sih_morbidade(  
  conjunto = "geral_internacao",  
  uf = NULL,  
  linha = NULL,  
  coluna = NULL,  
  conteudo = 1,  
  periodo = "last",  
  filtros = list()  
)
```

Arguments

conjunto	Dataset name listed by ‘datasus_catalogo("sih")’.
uf	Two-letter state abbreviation. ‘NULL’ uses the Brazil form.
linha	Row dimension. ‘NULL’ selects the form’s first dimension.
coluna	Column dimension. ‘NULL’ selects “Não ativa”.
conteudo	Measure label, raw TABNET value, or one-based index.
periodo	“last” for the latest competence, an exact period label or raw value, a four-digit year (all available competences in that year), or a vector of these values.
filtros	Named list of filters. Names and choices are available from [datasus_opcoes()].

Value

A data frame containing the TABNET result.

Examples

```
old_options <- options(  
  datasus.timeout = 5,  
  datasus.download_timeout = 15,  
  datasus.max_tries = 1  
)  
try({  
  sih_morbidade(uf = "MS")  
  sih_morbidade(  
    uf = "MS",  
    linha = "Capítulo CID-10",  
    conteudo = "Internações",  
    periodo = 2025  
  )  
})  
options(old_options)
```

sih_producao

Query hospital production from SIH/SUS

Description

Query hospital production from SIH/SUS

Usage

```
sih_producao(
  conjunto = "aih_rd_internacao",
  uf = NULL,
  linha = NULL,
  coluna = NULL,
  conteudo = 1,
  periodo = "last",
  filtros = list()
)
```

Arguments

conjunto	Dataset name listed by ‘datasus_catalogo("sih")’.
uf	Two-letter state abbreviation. ‘NULL’ uses the Brazil form.
linha	Row dimension. ‘NULL’ selects the form’s first dimension.
coluna	Column dimension. ‘NULL’ selects “Não ativa”.
conteudo	Measure label, raw TABNET value, or one-based index.
periodo	“last” for the latest competence, an exact period label or raw value, a four-digit year (all available competences in that year), or a vector of these values.
filtros	Named list of filters. Names and choices are available from [datasus_opcoes()].

Value

A data frame containing the TABNET result.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  sih_producao(uf = "MS")
  sih_producao(
    uf = "MS",
    linha = "Município",
```

```

    conteudo = "Internações",
    periodo = 2025,
    filtros = list(carater_atendimento = "Urgência")
  )
})
options(old_options)

```

sim

Query mortality data from SIM

Description

Provides a single interface to the mortality tables of the Mortality Information System (SIM). Available datasets are listed by `'datasus_catalogo("sim")'`; current row, column, measure, period and filter choices can be inspected with `'datasus_opcoes("sim", ...)'`.

Usage

```

sim(
  conjunto = "obitos",
  abrangencia = c("municipio", "uf"),
  uf = NULL,
  linha = NULL,
  coluna = NULL,
  conteudo = 1,
  periodo = "last",
  filtros = list()
)

```

Arguments

conjunto	SIM dataset: <code>"obitos"</code> , <code>"mortalidade_infantil"</code> , <code>"causas_evitaveis_0_4"</code> or <code>"causas_evitaveis_5_74"</code> .
abrangencia	Geographic form: <code>"municipio"</code> for municipality-level results or <code>"uf"</code> for region/state-level results.
uf	Optional state abbreviation, two-digit IBGE code or state name. With <code>'abrangencia = "municipio"'</code> , selects the state-specific municipal form. It must be <code>'NULL'</code> with <code>'abrangencia = "uf"'</code> .
linha	Row dimension. <code>'NULL'</code> selects the form's first dimension.
coluna	Column dimension. <code>'NULL'</code> selects <code>"Não ativa"</code> .
conteudo	Measure label, raw TABNET value or one-based index.
periodo	<code>"last"</code> for the latest available year, an exact period label or raw value, a four-digit year, or a vector of these values.
filtros	Named list of filters. Use <code>[datasus_opcoes()]</code> to inspect their names and accepted values.

Value

A data frame containing the TABNET result, with query provenance available through [datasus_proveniencia()].

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  datasus_catalogo("sim")
  op <- datasus_opcoes(
    "sim", "obitos", abrangencia = "uf"
  )
  obitos <- sim(
    conjunto = "obitos",
    abrangencia = "uf",
    periodo = 2024,
    filtros = list(sexo = "Masculino")
  )
})
options(old_options)
```

sim_evita10_bruf	Scrapes SIM's ICD-10 evitale causes data from regions
------------------	---

Description

This function allows the user to retrieve data from SIM's ICD-10 database much in the same way that is done by the online portal. The argument options refer to evitable causes data focused on the regions and states.

Usage

```
sim_evita10_bruf(linha = "Região", coluna = "Não ativa",
  conteudo = 1, periodo = "last", regioao = "all", unidade_da_federacao = "all",
  causas_evitaveis = "all", capitulo_cid10 = "all", categoria_cid10 = "all",
  faixa_etaria = "all", sexo = "all", cor_raca = "all", escolaridade = "all",
  estado_civil = "all", local_ocorrencia = "all")
```

Arguments

- linha A character describing which element will be displayed in the rows of the data.frame. Defaults to "Região".
- coluna A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".

conteudo	A character of length = 1 with the state's acronym of interest.
periodo	A character vector describing the period of data. Defaults to the last available.
regiao	"all" or a numeric vector with the IBGE's region codes to filter the data. Defaults to "all".
unidade_da_federacao	"all" or a numeric vector with the IBGE's state codes to filter the data. Defaults to "all".
causas_evitaveis	"all" or a character vector with the evitable cause code (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
capitulo_cid10	"all" or a numeric vector with the ICD-10 chapter to filter the data. Defaults to "all".
categoria_cid10	"all" or a character vector with the ICD-10 category codes (capital letter and two numbers) to filter the data. Defaults to "all".
faixa_etaria	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
sexo	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
cor_raca	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
escolaridade	"all" or a character vector with the instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
estado_civil	"all" or a character vector with the marital status (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
local_ocorrencia	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use 'sim()' or 'sinasc()' with a named 'filtros' list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also[sinasc_nv_uf](#)**Examples**

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  ## Requesting data from Midwest region
  sim_evita10_bruf(regiao = 5)
})
options(old_options)
```

sim_evita10_mun

*Scrapes SIM's ICD-10 evitable causes data from cities***Description**

This function allows the user to retrieve data from SIM's ICD-10 database much in the same way that is done by the online portal. The argument options refer to evitable causes data focused on Brazilian cities.

Usage

```
sim_evita10_mun(linha = "Município", coluna = "Não ativa",
  conteudo = 1, periodo = "last", municipio = "all", capital = "all",
  cir = "all", macrorregiao_de_saude = "all", microrregiao_ibge = "all",
  ride = "all", territorio_da_cidadania = "all", mesorregiao_pndr = "all",
  amazonia_legal = "all", semiarido = "all", faixa_de_frenteira = "all",
  zona_de_frenteira = "all", municipio_de_extrema_pobreza = "all",
  causas_evitaveis = "all", capitulo_cid10 = "all", categoria_cid10 = "all",
  faixa_etaria = "all", sexo = "all", cor_raca = "all", escolaridade = "all",
  estado_civil = "all", local_ocorrencia = "all")
```

Arguments

linha	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Município".
coluna	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
conteudo	A character of length = 1 with the state's acronym of interest.
periodo	A character vector describing the period of data. Defaults to the last available.

municipio	"all" or a numeric vector with the IBGE's city codes codes to filter the data. Defaults to "all".
capital	"all" or a numeric vector with the IBGE's cities codes to filter the data. Defaults to "all".
cir	"all" or a numeric vector with the CIR's codes to filter the data. Defaults to "all".
macrorregiao_de_saude	"all" or a numeric vector with the Health macro-region's codes to filter the data. Defaults to "all".
microrregiao_ibge	"all" or a numeric vector with the IBGE's micro-region codes to filter the data. Defaults to "all".
ride	"all" or a numeric vector with the IBGE's metropolitan-region codes to filter the data. Defaults to "all".
territorio_da_cidadania	"all" or a numeric vector with the territory of citizenship codes to filter the data. Defaults to "all".
mesorregiao_pndr	"all" or a numeric vector with the PNDR's mesoregion codes to filter the data. Defaults to "all".
amazonia_legal	"all" or a character ("Sim" or "Não") indicating if only the Legal Amazon region must be included. Defaults to "all".
semiarido	"all" or a character ("Sim" or "Não") indicating if only the semiarid region must be included. Defaults to "all".
faixa_de_frenteira	"all" or a character ("Sim" or "Não") indicating if only the border area must be included. Defaults to "all".
zona_de_frenteira	"all" or a character ("Sim" or "Não") indicating if only the border strip must be included. Defaults to "all".
municipio_de_extrema_pobreza	"all" or a character ("Sim" or "Não") indicating if only the municipalities of extreme poverty must be included. Defaults to "all".
causas_evitaveis	"all" or a character vector with the evitable cause code (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
capitulo_cid10	"all" or a numeric vector with the ICD-10 chapter to filter the data. Defaults to "all".
categoria_cid10	"all" or a character vector with the ICD-10 category codes (capital letter and two numbers) to filter the data. Defaults to "all".
faixa_etaria	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
sexo	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

cor_raca	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
escolaridade	"all" or a character vector with the instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
estado_civil	"all" or a character vector with the marital status (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
local_ocorrencia	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use `'sim()'` or `'sinasc()'` with a named `'filtros'` list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sinasc_nv_uf](#)

Examples

```
old_options <- options(  
  datasus.timeout = 5,  
  datasus.download_timeout = 15,  
  datasus.max_tries = 1  
)  
try({  
  ## Requesting data from the city of Campo Grande/MS  
  sim_evita10_mun(municipio = 500270)  
})  
options(old_options)
```

sim_evita10_uf

Scrapes SIM's ICD-10 evitable causes data from ufs

Description

This function allows the user to retrieve data from SIM's ICD-10 database much in the same way that is done by the online portal. The argument options refer to evitable causes in 0-4 age group data from the states unities.

Usage

```
sim_evita10_uf(uf, linha = "Município", coluna = "Não ativa",
  conteudo = 1, periodo = "last", municipio = "all", cir = "all",
  macrorregiao_de_saude = "all", divisao_admnist_estadual = "all",
  microrregiao_ibge = "all", ride = "all", causas_evitaveis = "all",
  capitulo_cid10 = "all", categoria_cid10 = "all", faixa_etaria = "all",
  sexo = "all", cor_raca = "all", escolaridade = "all", estado_civil = "all",
  local_ocorrencia = "all")
```

Arguments

uf	A character of length = 1 with the state's acronym of interest.
linha	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Município".
coluna	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
conteudo	A character of length = 1 with the state's acronym of interest.
periodo	A character vector describing the period of data. Defaults to the last available.
municipio	"all" or a numeric vector with the IBGE's city codes codes to filter the data. Defaults to "all".
cir	"all" or a numeric vector with the CIR's codes to filter the data. Defaults to "all".
macrorregiao_de_saude	"all" or a numeric vector with the Health macro-region's codes to filter the data. Defaults to "all".
divisao_admnist_estadual	"all" or a numeric vector with the State administrative division's codes to filter the data. Defaults to "all".
microrregiao_ibge	"all" or a numeric vector with the IBGE's micro-region codes to filter the data. Defaults to "all".
ride	"all" or a numeric vector with the IBGE's metropolitan-region codes to filter the data. Defaults to "all".
causas_evitaveis	"all" or a character vector with the evitable cause code (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

capitulo_cid10	"all" or a numeric vector with the ICD-10 chapter to filter the data. Defaults to "all".
categoria_cid10	"all" or a character vector with the ICD-10 category codes (capital letter and two numbers) to filter the data. Defaults to "all".
faixa_etaria	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
sexo	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
cor_raca	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
escolaridade	"all" or a character vector with the instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
estado_civil	"all" or a character vector with the marital status (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
local_ocorrencia	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use `'sim()'` or `'sinasc()'` with a named `'filtros'` list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sim_obt10_mun](#)

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
```

```
try({
## Requesting data from the state of Mato Grosso do Sul
sim_evita10_uf(uf = "ms")
})
options(old_options)
```

sim_evitb10_bruf

Scrapes SIM's ICD-10 evitale causes data from regions

Description

This function allows the user to retrieve data from SIM's ICD-10 database much in the same way that is done by the online portal. The argument options refer to evitable causes data focused on the regions and states and age ranging between 5-74 years old.

Usage

```
sim_evitb10_bruf(linha = "Região", coluna = "Não ativa",
  conteudo = 1, periodo = "last", regioao = "all", unidade_da_federacao = "all",
  causas_evitaveis = "all", capitulo_cid10 = "all", categoria_cid10 = "all",
  faixa_etaria = "all", faixa_etaria_detalhada = "all", sexo = "all",
  cor_raca = "all", escolaridade = "all", estado_civil = "all",
  local_ocorrencia = "all")
```

Arguments

linha	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Região".
coluna	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
conteudo	A character of length = 1 with the state's acronym of interest.
periodo	A character vector describing the period of data. Defaults to the last available.
regiao	"all" or a numeric vector with the IBGE's region codes to filter the data. Defaults to "all".
unidade_da_federacao	"all" or a numeric vector with the IBGE's state codes to filter the data. Defaults to "all".
causas_evitaveis	"all" or a character vector with the evitable cause code (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
capitulo_cid10	"all" or a numeric vector with the ICD-10 chapter to filter the data. Defaults to "all".

<code>categoria_cid10</code>	"all" or a character vector with the ICD-10 category codes (capital letter and two numbers) to filter the data. Defaults to "all".
<code>faixa_etaria</code>	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>faixa_etaria_detalhada</code>	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>sexo</code>	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>cor_raca</code>	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>escolaridade</code>	"all" or a character vector with the instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>estado_civil</code>	"all" or a character vector with the marital status (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>local_ocorrencia</code>	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use `'sim()'` or `'sinasc()'` with a named `'filtros'` list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sim_evita10_bruf](#)

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
```

```

    datasus.max_tries = 1
  )
  try({
    ## Requesting data from Midwest region
    sim_evitb10_bruf(region = 5)
  })
  options(old_options)

```

sim_evitb10_mun

Scrapes SIM's ICD-10 evitable causes data from cities

Description

This function allows the user to retrieve data from SIM's ICD-10 database much in the same way that is done by the online portal. The argument options refer to evitable causes data focused on brazilian cities and age ranging between 5-74 years old.

Usage

```

sim_evitb10_mun(linha = "Município", coluna = "Não ativa",
  conteudo = 1, periodo = "last", municipio = "all", capital = "all",
  cir = "all", macrorregiao_de_saude = "all", microrregiao_ibge = "all",
  ride = "all", territorio_da_cidadania = "all", mesorregiao_pndr = "all",
  amazonia_legal = "all", semiarido = "all", faixa_de_frenteira = "all",
  zona_de_frenteira = "all", municipio_de_extrema_pobreza = "all",
  causas_evitaveis = "all", capitulo_cid10 = "all", categoria_cid10 = "all",
  faixa_etaria = "all", faixa_etaria_detalhada = "all", sexo = "all",
  cor_raca = "all", escolaridade = "all", estado_civil = "all",
  local_ocorrencia = "all")

```

Arguments

linha	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Município".
coluna	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
conteudo	A character of length = 1 with the state's acronym of interest.
periodo	A character vector describing the period of data. Defaults to the last available.
municipio	"all" or a numeric vector with the IBGE's city codes codes to filter the data. Defaults to "all".
capital	"all" or a numeric vector with the IBGE's cities codes to filter the data. Defaults to "all".
cir	"all" or a numeric vector with the CIR's codes to filter the data. Defaults to "all".

macrorregiao_de_saude	"all" or a numeric vector with the Health macro-region's codes to filter the data. Defaults to "all".
microrregiao_ibge	"all" or a numeric vector with the IBGE's micro-region codes to filter the data. Defaults to "all".
ride	"all" or a numeric vector with the IBGE's metropolitan-region codes to filter the data. Defaults to "all".
territorio_da_cidadania	"all" or a numeric vector with the territory of citizenship codes to filter the data. Defaults to "all".
mesorregiao_pndr	"all" or a numeric vector with the PNDR's mesoregion codes to filter the data. Defaults to "all".
amazonia_legal	"all" or a character ("Sim" or "Não") indicating if only the Legal Amazon region must be included. Defaults to "all".
semiarido	"all" or a character ("Sim" or "Não") indicating if only the semiarid region must be included. Defaults to "all".
faixa_de_frenteira	"all" or a character ("Sim" or "Não") indicating if only the border area must be included. Defaults to "all".
zona_de_frenteira	"all" or a character ("Sim" or "Não") indicating if only the border strip must be included. Defaults to "all".
municipio_de_extrema_pobreza	"all" or a character ("Sim" or "Não") indicating if only the municipalities of extreme poverty must be included. Defaults to "all".
causas_evitaveis	"all" or a character vector with the evitable cause code (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
capitulo_cid10	"all" or a numeric vector with the ICD-10 chapter to filter the data. Defaults to "all".
categoria_cid10	"all" or a character vector with the ICD-10 category codes (capital letter and two numbers) to filter the data. Defaults to "all".
faixa_etaria	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_detalhada	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
sexo	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

cor_raca	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
escolaridade	"all" or a character vector with the instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
estado_civil	"all" or a character vector with the marital status (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
local_ocorrencia	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use `'sim()'` or `'sinasc()'` with a named `'filtros'` list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sim_evita10_mun](#)

Examples

```
old_options <- options(  
  datasus.timeout = 5,  
  datasus.download_timeout = 15,  
  datasus.max_tries = 1  
)  
try({  
  ## Requesting data from the city of Campo Grande/MS  
  sim_evitb10_mun(municipio = 500270)  
})  
options(old_options)
```

sim_evitb10_uf

Scrapes SIM's ICD-10 evitable causes data from ufs

Description

This function allows the user to retrieve data from SIM's ICD-10 database much in the same way that is done by the online portal. The argument options refer to evitable causes in 5-74 age group data from the states unities.

Usage

```
sim_evitb10_uf(uf, linha = "Município", coluna = "Não ativa",
  conteudo = 1, periodo = "last", municipio = "all", cir = "all",
  macrorregiao_de_saude = "all", divisao_admnist_estadual = "all",
  microrregiao_ibge = "all", ride = "all", causas_evitaveis = "all",
  capitulo_cid10 = "all", categoria_cid10 = "all", faixa_etaria = "all",
  faixa_etaria_detalhada = "all", sexo = "all", cor_raca = "all",
  escolaridade = "all", estado_civil = "all", local_ocorrencia = "all")
```

Arguments

uf	A character of length = 1 with the state's acronym of interest.
linha	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Município".
coluna	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
conteudo	A character of length = 1 with the state's acronym of interest.
periodo	A character vector describing the period of data. Defaults to the last available.
municipio	"all" or a numeric vector with the IBGE's city codes codes to filter the data. Defaults to "all".
cir	"all" or a numeric vector with the CIR's codes to filter the data. Defaults to "all".
macrorregiao_de_saude	"all" or a numeric vector with the Health macro-region's codes to filter the data. Defaults to "all".
divisao_admnist_estadual	"all" or a numeric vector with the State administrative division's codes to filter the data. Defaults to "all".
microrregiao_ibge	"all" or a numeric vector with the IBGE's micro-region codes to filter the data. Defaults to "all".
ride	"all" or a numeric vector with the IBGE's metropolitan-region codes to filter the data. Defaults to "all".
causas_evitaveis	"all" or a character vector with the evitable cause code (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

capitulo_cid10	"all" or a numeric vector with the ICD-10 chapter to filter the data. Defaults to "all".
categoria_cid10	"all" or a character vector with the ICD-10 category codes (capital letter and two numbers) to filter the data. Defaults to "all".
faixa_etaria	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_detalhada	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
sexo	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
cor_raca	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
escolaridade	"all" or a character vector with the instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
estado_civil	"all" or a character vector with the marital status (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
local_ocorrencia	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use `'sim()'` or `'sinasc()'` with a named `'filtros'` list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sim_evita10_uf](#)

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  ## Requesting data from the state of Mato Grosso do Sul
  sim_evitb10_uf(uf = "ms")
})
options(old_options)
```

sim_inf10_bruf

Scrapes SIM's ICD-10 child mortality data from regions

Description

This function allows the user to retrieve data from SIM's ICD-10 database much in the same way that is done by the online portal. The argument options refer to child mortality data focused on focused on the regions and states.

Usage

```
sim_inf10_bruf(linha = "Região", coluna = "Não ativa",
  conteudo = 1, periodo = "last", regioao = "all",
  unidade_da_federacao = "all", capitulo_cid10 = "all",
  categoria_cid10 = "all", lista_mort_cid10 = "all",
  causa_mal_definidas = "all", causas_evitaveis_0a4anos = "all",
  faixa_etaria_1 = "all", faixa_etaria_2 = "all", faixa_etaria_3 = "all",
  faixa_etaria_4 = "all", faixa_etaria_5 = "all",
  faixa_etaria_detalhada = "all", sexo = "all", cor_raca = "all",
  local_ocorrencia = "all", idade_mae = "all", escolaridade_mae = "all",
  duracao_gestacao = "all", tipo_gravidez = "all", tipo_parto = "all",
  peso_ao_nascer = "all", obito_relacao_parto = "all",
  obito_investigado = "all")
```

Arguments

linha	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Município".
coluna	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
conteudo	A character of length = 1 with the state's acronym of interest.
periodo	A character vector describing the period of data. Defaults to the last available.

regiao	"all" or a numeric vector with the IBGE's region codes to filter the data. Defaults to "all".
unidade_da_federacao	"all" or a numeric vector with the IBGE's state codes to filter the data. Defaults to "all".
capitulo_cid10	"all" or a numeric vector with the ICD-10 chapter to filter the data. Defaults to "all".
categoria_cid10	"all" or a character vector with the ICD-10 category codes (capital letter and two numbers) to filter the data. Defaults to "all".
lista_mort_cid10	"all" or a character vector with the mortality type (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
causa_mal_definidas	"all" or a character vector with the ill-defined causes (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
causas_evitaveis_0a4anos	"all" or a character vector with the evitable cause code (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_1	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_2	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_3	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_4	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_5	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_detalhada	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
sexo	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
cor_raca	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

local_ocorrencia	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".
idade_mae	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
escolaridade_mae	"all" or a character vector with the mother's instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
duracao_gestacao	"all" or a character vector with the marital status of the mother (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
tipo_gravidez	"all" or a character vector with the type of pregnancy (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
tipo_parto	"all" or a character vector with the Parturition type (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
peso_ao_nascer	"all" or a character vector with the birth weight (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
obito_relacao_parto	"all" or a character vector with period of child mortality in relation to childbirth (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
obito_investigado	"all" or a character vector indicating if the death was investigated (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use `sim()` or `sinasc()` with a named `'filtros'` list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sim_evita10_mun](#)

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  ## Requesting data from Midwest region
  sim_inf10_bruf(regiao = 5)
})
options(old_options)
```

sim_inf10_mun

Scrapes SIM's ICD-10 child mortality data from cities

Description

This function allows the user to retrieve data from SIM's ICD-10 database much in the same way that is done by the online portal. The argument options refer to child mortality data focused on Brazilian cities.

Usage

```
sim_inf10_mun(linha = "Município", coluna = "Não ativa",
  conteudo = 1, periodo = "last", municipio = "all", capital = "all",
  cir = "all", macrorregiao_de_saude = "all", microrregiao_ibge = "all",
  ride = "all", territorio_da_cidadania = "all", mesorregiao_pndr = "all",
  amazonia_legal = "all", semiarido = "all", faixa_de_frenteira = "all",
  zona_de_frenteira = "all", municipio_de_extrema_pobreza = "all",
  capitulo_cid10 = "all", categoria_cid10 = "all", lista_mort_cid10 = "all",
  causa_mal_definidas = "all", causas_evitaveis_0a4anos = "all",
  faixa_etaria_1 = "all", faixa_etaria_2 = "all", faixa_etaria_3 = "all",
  faixa_etaria_4 = "all", faixa_etaria_5 = "all", faixa_etaria_detalhada = "all",
  sexo = "all", cor_raca = "all", local_ocorrencia = "all", idade_mae = "all",
  escolaridade_mae = "all", duracao_gestacao = "all", tipo_gravidez = "all",
  tipo_parto = "all", peso_ao_nascer = "all", obito_relacao_parto = "all",
  obito_investigado = "all")
```

Arguments

linha	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Município".
coluna	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
conteudo	A character of length = 1 with the state's acronym of interest.

periodo	A character vector describing the period of data. Defaults to the last available.
municipio	"all" or a numeric vector with the IBGE's city codes codes to filter the data. Defaults to "all".
capital	"all" or a numeric vector with the IBGE's cities codes to filter the data. Defaults to "all".
cir	"all" or a numeric vector with the CIR's codes to filter the data. Defaults to "all".
macrorregiao_de_saude	"all" or a numeric vector with the Health macro-region's codes to filter the data. Defaults to "all".
microrregiao_ibge	"all" or a numeric vector with the IBGE's micro-region codes to filter the data. Defaults to "all".
ride	"all" or a numeric vector with the IBGE's metropolitan-region codes to filter the data. Defaults to "all".
territorio_da_cidadania	"all" or a numeric vector with the territory of citizenship codes to filter the data. Defaults to "all".
mesorregiao_pndr	"all" or a numeric vector with the PNDR's mesoregion codes to filter the data. Defaults to "all".
amazonia_legal	"all" or a character ("Sim" or "Não") indicating if only the Legal Amazon region must be included. Defaults to "all".
semiarido	"all" or a character ("Sim" or "Não") indicating if only the semiarid region must be included. Defaults to "all".
faixa_de_frenteira	"all" or a character ("Sim" or "Não") indicating if only the border area must be included. Defaults to "all".
zona_de_frenteira	"all" or a character ("Sim" or "Não") indicating if only the border strip must be included. Defaults to "all".
municipio_de_extrema_pobreza	"all" or a character ("Sim" or "Não") indicating if only the municipalities of extreme poverty must be included. Defaults to "all".
capitulo_cid10	"all" or a numeric vector with the ICD-10 chapter to filter the data. Defaults to "all".
categoria_cid10	"all" or a character vector with the ICD-10 category codes (capital letter and two numbers) to filter the data. Defaults to "all".
lista_mort_cid10	"all" or a character vector with the mortality type (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
causa_mal_definidas	"all" or a character vector with the ill-defined causes (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

causas_evitaveis_0a4anos	"all" or a character vector with the evitable cause code (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_1	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_2	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_3	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_4	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_5	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_detalhada	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
sexo	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
cor_raca	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
local_ocorrencia	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".
idade_mae	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
escolaridade_mae	"all" or a character vector with the mother's instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
duracao_gestacao	"all" or a character vector with the marital status of the mother (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
tipo_gravidez	"all" or a character vector with the type of pregnancy (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

tipo_parto "all" or a character vector with the Parturition type (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

peso_ao_nascer "all" or a character vector with the birth weight (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

obito_relacao_parto "all" or a character vector with period of child mortality in relation to childbirth (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

obito_investigado "all" or a character vector indicating if the death was investigated (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use `'sim()'` or `'sinasc()'` with a named `'filtros'` list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sim_evita10_mun](#)

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  ## Requesting data from the city of Campo Grande/MS
  sim_inf10_mun(municipio = 500270)
})
options(old_options)
```

sim_inf10_uf

*Scrapes SIM's ICD-10 child mortality data from ufs***Description**

This function allows the user to retrieve data from SIM's ICD-10 database much in the same way that is done by the online portal. The argument options refer to child mortality data from the states unities.

Usage

```
sim_inf10_uf(uf, linha = "Município", coluna = "Não ativa",
  conteudo = 1, periodo = "last", municipio = "all", cir = "all",
  macrorregiao_de_saude = "all", divisao_admnist_estadual = "all",
  microrregiao_ibge = "all", ride = "all", capitulo_cid10 = "all",
  categoria_cid10 = "all", lista_mort_cid10 = "all",
  causa_mal_definidas = "all", faixa_etaria_1 = "all",
  faixa_etaria_2 = "all", faixa_etaria_3 = "all", faixa_etaria_4 = "all",
  faixa_etaria_5 = "all", faixa_etaria_detalhada = "all",
  sexo = "all", cor_raca = "all", local_ocorrencia = "all",
  idade_mae = "all", escolaridade_mae = "all",
  duracao_gestacao = "all", tipo_gravidez = "all", tipo_parto = "all",
  peso_ao_nascer = "all", obito_relacao_parto = "all",
  obito_investigado = "all")
```

Arguments

uf	A character of length = 1 with the state "all".
linha	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Município".
coluna	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
conteudo	A character of length = 1 with the state's acronym of interest.
periodo	A character vector describing the period of data. Defaults to the last available.
municipio	"all" or a numeric vector with the IBGE's city codes codes to filter the data. Defaults to "all".
cir	"all" or a numeric vector with the CIR's codes to filter the data. Defaults to "all".
macrorregiao_de_saude	"all" or a numeric vector with the Health macro-region's codes to filter the data. Defaults to "all".
divisao_admnist_estadual	"all" or a numeric vector with the State administrative division's codes to filter the data. Defaults to "all".
microrregiao_ibge	"all" or a numeric vector with the IBGE's micro-region codes to filter the data. Defaults to "all".

<code>ride</code>	"all" or a numeric vector with the IBGE's metropolitan-region codes to filter the data. Defaults to "all".
<code>capitulo_cid10</code>	"all" or a numeric vector with the ICD-10 chapter to filter the data. Defaults to "all".
<code>categoria_cid10</code>	"all" or a character vector with the ICD-10 category codes (capital letter and two numbers) to filter the data. Defaults to "all".
<code>lista_mort_cid10</code>	"all" or a character vector with the mortality type (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>causa_mal_definidas</code>	"all" or a character vector with the ill-defined causes (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>faixa_etaria_1</code>	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>faixa_etaria_2</code>	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>faixa_etaria_3</code>	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>faixa_etaria_4</code>	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>faixa_etaria_5</code>	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>faixa_etaria_detalhada</code>	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>sexo</code>	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>cor_raca</code>	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>local_ocorrencia</code>	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".
<code>idade_mae</code>	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

escolaridade_mae "all" or a character vector with the mother's instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

duracao_gestacao "all" or a character vector with the marital status of the mother (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

tipo_gravidez "all" or a character vector with the type of pregnancy (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

tipo_parto "all" or a character vector with the Parturition type (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

peso_ao_nascer "all" or a character vector with the birth weight (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

obito_relacao_parto "all" or a character vector with period of child mortality in relation to childbirth (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

obito_investigado "all" or a character vector indicating if the death was investigated (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use `'sim()'` or `'sinasc()'` with a named `'filtros'` list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sim_evita10_uf](#)

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
```

```
)
try({
## Requesting data from the state of Mato Grosso do Sul
sim_inf10_uf(uf = "ms")
})
options(old_options)
```

sim_microdados	<i>Read SIM death microdata</i>
----------------	---------------------------------

Description

Read SIM death microdata

Usage

```
sim_microdados(ano, uf = NULL, tipo = "DO", ...)
```

Arguments

- ano One or more years.
- uf One or more state abbreviations.
- tipo SIM file type, default "DO".
- ... Additional arguments passed to [microdados_ler()].

Value

Record-level SIM data.

sim_obt10_bruf	<i>Scrapes SIM's ICD-10 data from regions</i>
----------------	---

Description

This function allows the user to retrieve data from SIM's ICD-10 database much in the same way that is done by the online portal. The argument options refer to data focused on the regions and states.

Usage

```
sim_obt10_bruf(linha = "Região", coluna = "Não ativa",
  conteudo = 1, periodo = "last", regioao = "all", unidade_da_federacao = "all",
  capitulo_cid10 = "all", grupo_cid10 = "all", categoria_cid10 = "all",
  causa_br_cid10 = "all", causa_mal_definida = "all", faixa_etaria = "all",
  faixa_etaria_ops = "all", faixa_etaria_det = "all", faixa_etaria_menor1a = "all",
  sexo = "all", cor_raca = "all", escolaridade = "all", estado_civil = "all",
  local_ocorrencia = "all")
```

Arguments

linha	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Região".
coluna	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
conteudo	A character of length = 1 with the state's acronym of interest.
periodo	A character vector describing the period of data. Defaults to the last available.
regiao	"all" or a numeric vector with the IBGE's region codes to filter the data. Defaults to "all".
unidade_da_federacao	"all" or a numeric vector with the IBGE's state codes to filter the data. Defaults to "all".
capitulo_cid10	"all" or a numeric vector with the ICD-10 chapter to filter the data. Defaults to "all".
grupo_cid10	"all" or a character vector with the ICD-10 group (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
categoria_cid10	"all" or a character vector with the ICD-10 category codes (capital letter and two numbers) to filter the data. Defaults to "all".
causa_br_cid10	"all" or a character vector with the ICD-10 cause codes to filter the data. Defaults to "all".
causa_mal_definida	"all" or a character vector with the ill-defined causes (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_ops	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all". "ops" in the argument name stands for Pan American Health Organization.

faixa_etaria_det	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_menor1a	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
sexo	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
cor_raca	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
escolaridade	"all" or a character vector with the instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
estado_civil	"all" or a character vector with the marital status (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
local_ocorrencia	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use `'sim()'` or `'sinasc()'` with a named `'filtros'` list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sinasc_nv_uf](#)

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
```

```
## Requesting data from Midwest region
sim_obt10_bruf(region = 5)
})
options(old_options)
```

sim_obt10_mun

Scrapes SIM's ICD-10 data from cities

Description

This function allows the user to retrieve data from SIM's ICD-10 database much in the same way that is done by the online portal. The argument options refer to data focused on brazilian cities.

Usage

```
sim_obt10_mun(linha = "Município", coluna = "Não ativa",
  conteudo = 1, periodo = "last", municipio = "all", capital = "all",
  cir = "all", macrorregiao_de_saude = "all", microrregiao_ibge = "all",
  ride = "all", territorio_da_cidadania = "all", mesorregiao_pndr = "all",
  amazonia_legal = "all", semiarido = "all", faixa_de_frenteira = "all",
  zona_de_frenteira = "all", municipio_de_extrema_pobreza = "all",
  capitulo_cid10 = "all", grupo_cid10 = "all", categoria_cid10 = "all",
  causa_br_cid10 = "all", causa_mal_definida = "all", faixa_etaria = "all",
  faixa_etaria_ops = "all", faixa_etaria_det = "all", faixa_etaria_menor1a = "all",
  sexo = "all", cor_raca = "all", escolaridade = "all", estado_civil = "all",
  local_ocorrencia = "all")
```

Arguments

linha	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Município".
coluna	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
conteudo	A character of length = 1 with the state's acronym of interest.
periodo	A character vector describing the period of data. Defaults to the last available.
municipio	"all" or a numeric vector with the IBGE's city codes codes to filter the data. Defaults to "all".
capital	"all" or a numeric vector with the IBGE's cities codes to filter the data. Defaults to "all".
cir	"all" or a numeric vector with the CIR's codes to filter the data. Defaults to "all".
macrorregiao_de_saude	"all" or a numeric vector with the Health macro-region's codes to filter the data. Defaults to "all".

microrregiao_ibge	"all" or a numeric vector with the IBGE's micro-region codes to filter the data. Defaults to "all".
ride	"all" or a numeric vector with the IBGE's metropolitan-region codes to filter the data. Defaults to "all".
territorio_da_cidadania	"all" or a numeric vector with the territory of citizenship codes to filter the data. Defaults to "all".
mesorregiao_pndr	"all" or a numeric vector with the PNDR's mesoregion codes to filter the data. Defaults to "all".
amazonia_legal	"all" or a character ("Sim" or "Não") indicating if only the Legal Amazon region must be included. Defaults to "all".
semiario	"all" or a character ("Sim" or "Não") indicating if only the semiarid region must be included. Defaults to "all".
faixa_de_frenteira	"all" or a character ("Sim" or "Não") indicating if only the border area must be included. Defaults to "all".
zona_de_frenteira	"all" or a character ("Sim" or "Não") indicating if only the border strip must be included. Defaults to "all".
municipio_de_extrema_pobreza	"all" or a character ("Sim" or "Não") indicating if only the municipalities of extreme poverty must be included. Defaults to "all".
capitulo_cid10	"all" or a numeric vector with the ICD-10 chapter to filter the data. Defaults to "all".
grupo_cid10	"all" or a character vector with the ICD-10 group (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
categoria_cid10	"all" or a character vector with the ICD-10 category codes (capital letter and two numbers) to filter the data. Defaults to "all".
causa_br_cid10	"all" or a character vector with the ICD-10 cause codes to filter the data. Defaults to "all".
causa_mal_definida	"all" or a character vector with the ill-defined causes (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_ops	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all". "ops" in the argument name stands for Pan American Health Organization.

faixa_etaria_det	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_menor1a	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
sexo	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
cor_raca	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
escolaridade	"all" or a character vector with the instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
estado_civil	"all" or a character vector with the marital status (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
local_ocorrencia	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use `'sim()'` or `'sinasc()'` with a named `'filtros'` list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sinasc_nv_uf](#)

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
```

```
## Requesting data from the city of Campo Grande/MS
sim_obt10_mun(municipio = 500270)
})
options(old_options)
```

sim_obt10_uf

Scrapes SIM's ICD-10 data from UF's

Description

This function allows the user to retrieve data from SIM's ICD-10 database much in the same way that is done by the online portal. The argument options refer to data from the states unities.

Usage

```
sim_obt10_uf(uf, linha = "Município", coluna = "Não ativa",
  conteudo = 1, periodo = "last", municipio = "all", cir = "all",
  macrorregiao_de_saude = "all", divisao_admnist_estadual = "all",
  microrregiao_ibge = "all", ride = "all", capitulo_cid10 = "all",
  grupo_cid10 = "all", categoria_cid10 = "all", causa_br_cid10 = "all",
  causa_mal_definida = "all", faixa_etaria = "all", faixa_etaria_ops = "all",
  faixa_etaria_det = "all", faixa_etaria_menor1a = "all", sexo = "all",
  cor_raca = "all", escolaridade = "all", estado_civil = "all",
  local_ocorrencia = "all")
```

Arguments

uf	A character of length = 1 with the state's acronym of interest.
linha	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Município".
coluna	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
conteudo	A character of length = 1 with the state's acronym of interest.
periodo	A character vector describing the period of data. Defaults to the last available.
municipio	"all" or a numeric vector with the IBGE's city codes codes to filter the data. Defaults to "all".
cir	"all" or a numeric vector with the CIR's codes to filter the data. Defaults to "all".
macrorregiao_de_saude	"all" or a numeric vector with the Health macro-region's codes to filter the data. Defaults to "all".
divisao_admnist_estadual	"all" or a numeric vector with the State administrative division's codes to filter the data. Defaults to "all".

microrregiao_ibge	"all" or a numeric vector with the IBGE's micro-region codes to filter the data. Defaults to "all".
ride	"all" or a numeric vector with the IBGE's metropolitan-region codes to filter the data. Defaults to "all".
capitulo_cid10	"all" or a numeric vector with the ICD-10 chapter to filter the data. Defaults to "all".
grupo_cid10	"all" or a character vector with the ICD-10 group (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
categoria_cid10	"all" or a character vector with the ICD-10 category codes (capital letter and two numbers) to filter the data. Defaults to "all".
causa_br_cid10	"all" or a character vector with the ICD-10 cause codes to filter the data. Defaults to "all".
causa_mal_definida	"all" or a character vector with the ill-defined causes (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_ops	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all". "ops" in the argument name stands for Pan American Health Organization.
faixa_etaria_det	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
faixa_etaria_menor1a	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
sexo	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
cor_raca	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
escolaridade	"all" or a character vector with the instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
estado_civil	"all" or a character vector with the marital status (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

`local_ocorrencia`

"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use `'sim()'` or `'sinasc()'` with a named `'filtros'` list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sim_obt10_mun](#)

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  ## Requesting data from the state of Mato Grosso do Sul
  sim_obt10_uf(uf = "ms")
})
options(old_options)
```

sinan

Query notifiable diseases and conditions from SINAN

Description

Supports the disease-specific TABNET datasets listed by `'datasus_catalogo("sinan")'`. Because each disease has its own form, inspect dimensions, periods and filters with `'datasus_opcoes("sinan", agravo)'`. Febre amarela is not included because its official link points to a separate open-data platform rather than a TABNET form.

Usage

```
sinan(  
  agravo = "dengue",  
  uf = NULL,  
  linha = NULL,  
  coluna = NULL,  
  conteudo = 1,  
  periodo = "last",  
  filtros = list()  
)
```

Arguments

agravo	Notifiable disease or condition listed by ‘datasus_catalogo("sinan")’.
uf	Two-letter state abbreviation. ‘NULL’ uses the Brazil form.
linha	Row dimension. ‘NULL’ selects the form’s first dimension.
coluna	Column dimension. ‘NULL’ selects “Não ativa”.
conteudo	Measure label, raw TABNET value, or one-based index.
periodo	“last” for the latest available period, an exact period label or raw value, a four-digit year, or a vector of these values.
filtros	Named list of filters. Names and choices are available from [datasus_opcoes()].

Value

A data frame containing the TABNET result.

Examples

```
old_options <- options(  
  datasus.timeout = 5,  
  datasus.download_timeout = 15,  
  datasus.max_tries = 1  
)  
try({  
  sinan("dengue", uf = "MS")  
  sinan(  
    "violencia_interpessoal_autoprovocada",  
    uf = "MS",  
    periodo = 2024  
  )  
})  
options(old_options)
```

sinan_dengue	<i>Read current SINAN dengue microdata</i>
--------------	--

Description

Downloads the annual OpenDataSUS resources. This complements the aggregated legacy TABNET interface available from `'sinan("dengue")'`.

Usage

```
sinan_dengue(
  ano = "last",
  formato = "CSV",
  destino = NULL,
  cache = TRUE,
  atualizar = FALSE,
  n_max = Inf,
  ...
)
```

Arguments

ano	Dataset year or <code>"last"</code> .
formato	<code>"CSV"</code> or <code>"JSON"</code> .
destino	Optional destination file or existing directory.
cache	Whether to reuse the local cache.
atualizar	Whether to force a new metadata query and download.
n_max	Maximum number of CSV rows to read.
...	Additional arguments passed to the underlying reader.

Value

The parsed OpenDataSUS resource.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  dengue <- sinan_dengue(ano = 2025, n_max = 1000)
})
options(old_options)
```

sinan_mpox	<i>Read current e-SUS SINAN Mpox microdata</i>
------------	--

Description

Read current e-SUS SINAN Mpox microdata

Usage

```
sinan_mpox(  
  ano = "last",  
  formato = "CSV",  
  destino = NULL,  
  cache = TRUE,  
  atualizar = FALSE,  
  n_max = Inf,  
  ...  
)
```

Arguments

ano	Dataset year or "last".
formato	"CSV" or "JSON".
destino	Optional destination file or existing directory.
cache	Whether to reuse the local cache.
atualizar	Whether to force a new metadata query and download.
n_max	Maximum number of CSV rows to read.
...	Additional arguments passed to the underlying reader.

Value

The parsed OpenDataSUS resource.

Examples

```
old_options <- options(  
  datasus.timeout = 5,  
  datasus.download_timeout = 15,  
  datasus.max_tries = 1  
)  
try({  
  cases <- sinan_mpox(ano = 2025, n_max = 1000)  
})  
options(old_options)
```

sinasc

*Query live-birth data from SINASC***Description**

Provides a single interface to the Live Birth Information System (SINASC). Current row, column, measure, period and filter choices can be inspected with `'datasus_opcoes("sinasc", ...).'`

Usage

```
sinasc(
  conjunto = "nascidos_vivos",
  abrangencia = c("municipio", "uf"),
  uf = NULL,
  linha = NULL,
  coluna = NULL,
  conteudo = 1,
  periodo = "last",
  filtros = list()
)
```

Arguments

conjunto	SINASC dataset. Currently <code>"nascidos_vivos"</code> .
abrangencia	Geographic form: <code>"municipio"</code> for municipality-level results or <code>"uf"</code> for region/state-level results.
uf	Optional state abbreviation, two-digit IBGE code or state name. With <code>'abrangencia = "municipio"'</code> , selects the state-specific municipal form. It must be <code>'NULL'</code> with <code>'abrangencia = "uf"'</code> .
linha	Row dimension. <code>'NULL'</code> selects the form's first dimension.
coluna	Column dimension. <code>'NULL'</code> selects <code>"Não ativa"</code> .
conteudo	Measure label, raw TABNET value or one-based index.
periodo	<code>"last"</code> for the latest available year, an exact period label or raw value, a four-digit year, or a vector of these values.
filtros	Named list of filters. Use <code>[datasus_opcoes()]</code> to inspect their names and accepted values.

Value

A data frame containing the TABNET result, with query provenance available through `[datasus_proveniencia()]`.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  op <- datasus_opcoes(
    "sinasc", abrangencia = "municipio", uf = "SP"
  )
  nascimentos <- sinasc(
    uf = "SP",
    periodo = 2024,
    filtros = list(sexo = "Masculino")
  )
})
options(old_options)
```

sinasc_microdados

*Read SINASC live birth microdata***Description**

Read SINASC live birth microdata

Usage

```
sinasc_microdados(ano, uf = NULL, tipo = "DN", ...)
```

Arguments

<code>ano</code>	One or more years.
<code>uf</code>	One or more state abbreviations.
<code>tipo</code>	SIM file type, default "DO".
<code>...</code>	Additional arguments passed to <code>[microdados_ler()]</code> .

Value

Record-level SINASC data.

sinasc_nv_bruf

*Scrapes SINASC data from regions***Description**

This function allows the user to retrieve data from SINASC database much in the same way that is done by the online portal. The argument options refer to data focused on the regions and states.

Usage

```
sinasc_nv_bruf(linha = "Região", coluna = "Não ativa",
  conteudo = 1, periodo = "last", regioao = "all", unidade_da_federacao = "all",
  local_ocorrencia = "all", idade_da_mae = "all", instrucao_da_mae = "all",
  estado_civil_mae = "all", duracao_gestacao = "all", tipo_de_gravidez = "all",
  tipo_de_parto = "all", consult_pre_natal = "all", sexo = "all",
  cor_raca = "all", apgar_1_minuto = "all", apgar_5_minuto = "all",
  peso_ao_nascer = "all", anomalia_congenita = "all", tipo_anomal_congen = "all")
```

Arguments

linha	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Município".
coluna	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
conteudo	A character of length = 1 with the state's acronym of interest.
periodo	A character vector describing the period of data. Defaults to the last available.
regiao	"all" or a numeric vector with the IBGE's region codes to filter the data. Defaults to "all".
unidade_da_federacao	"all" or a numeric vector with the IBGE's state codes to filter the data. Defaults to "all".
local_ocorrencia	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".
idade_da_mae	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
instrucao_da_mae	"all" or a character vector with the mother's instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
estado_civil_mae	"all" or a character vector with the marital status of the mother (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

<code>duracao_gestacao</code>	"all" or a character vector with the marital status of the mother (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>tipo_de_gravidez</code>	"all" or a character vector with the type of pregnancy (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>tipo_de_parto</code>	"all" or a character vector with the Parturition type (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>consult_pre_natal</code>	"all" or a character vector with the amount of prenatal consultation (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>sexo</code>	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>cor_raca</code>	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>apgar_1_minuto</code>	"all" or a character vector with the value of the apgar exam of the first minute (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>apgar_5_minuto</code>	"all" or a character vector with the value of the apgar exam of the fifth minute (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>peso_ao_nascer</code>	"all" or a character vector with the birth weight (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>anomalia_congenita</code>	"all" or a character vector with the indicative of congenital anomaly (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>tipo_anomal_congen</code>	"all" or a character vector with the congenital anomaly type (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use `sim()` or `sinasc()` with a named `'filtros'` list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sinasc_nv_uf](#)

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  ## Requesting data from Midwest region
  sinasc_nv_bruf(region = 5)
})
options(old_options)
```

sinasc_nv_mun

Scrapes SINASC data from cities

Description

This function allows the user to retrieve data from SINASC database much in the same way that is done by the online portal. The argument options refer to data focused on Brazilian cities.

Usage

```
sinasc_nv_mun(linha = "Município", coluna = "Não ativa",
  conteudo = 1, periodo = "last", municipio = "all", capital = "all",
  cir = "all", macrorregiao_de_saude = "all", microrregiao_ibge = "all",
  ride = "all", territorio_da_cidadania = "all", mesorregiao_pndr = "all",
  amazonia_legal = "all", semiarido = "all", faixa_de_frenteira = "all",
  zona_de_frenteira = "all", municipio_de_extrema_pobreza = "all",
  local_ocorrencia = "all", idade_da_mae = "all", instrucao_da_mae = "all",
  estado_civil_mae = "all", duracao_gestacao = "all", tipo_de_gravidez = "all",
  tipo_de_parto = "all", consult_pre_natal = "all", sexo = "all", cor_raca = "all",
  apgar_1_minuto = "all", apgar_5_minuto = "all", peso_ao_nascer = "all",
  anomalia_congenita = "all", tipo_anomal_congen = "all")
```

Arguments

linha	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Município".
coluna	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
conteudo	A character of length = 1 with the state's acronym of interest.
periodo	A character vector describing the period of data. Defaults to the last available.
municipio	"all" or a numeric vector with the IBGE's city codes codes to filter the data. Defaults to "all".
capital	"all" or a numeric vector with the IBGE's cities codes to filter the data. Defaults to "all".
cir	"all" or a numeric vector with the CIR's codes to filter the data. Defaults to "all".
macrorregiao_de_saude	"all" or a numeric vector with the Health macro-region's codes to filter the data. Defaults to "all".
microrregiao_ibge	"all" or a numeric vector with the IBGE's micro-region codes to filter the data. Defaults to "all".
ride	"all" or a numeric vector with the IBGE's metropolitan-region codes to filter the data. Defaults to "all".
territorio_da_cidadania	"all" or a numeric vector with the territory of citizenship codes to filter the data. Defaults to "all".
mesorregiao_pndr	"all" or a numeric vector with the PNDR's mesoregion codes to filter the data. Defaults to "all".
amazonia_legal	"all" or a character ("Sim" or "Não") indicating if only the Legal Amazon region must be included. Defaults to "all".
semiarido	"all" or a character ("Sim" or "Não") indicating if only the semiarid region must be included. Defaults to "all".
faixa_de_frenteira	"all" or a character ("Sim" or "Não") indicating if only the border area must be included. Defaults to "all".
zona_de_frenteira	"all" or a character ("Sim" or "Não") indicating if only the border strip must be included. Defaults to "all".
municipio_de_extrema_pobreza	"all" or a character ("Sim" or "Não") indicating if only the municipalities of extreme poverty must be included. Defaults to "all".
local_ocorrencia	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".
idade_da_mae	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

<code>instrucao_da_mae</code>	"all" or a character vector with the mother's instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>estado_civil_mae</code>	"all" or a character vector with the marital status of the mother (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>duracao_gestacao</code>	"all" or a character vector with the marital status of the mother (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>tipo_de_gravidez</code>	"all" or a character vector with the type of pregnancy (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>tipo_de_parto</code>	"all" or a character vector with the Parturition type (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>consult_pre_natal</code>	"all" or a character vector with the amount of prenatal consultation (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>sexo</code>	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>cor_raca</code>	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>apgar_1_minuto</code>	"all" or a character vector with the value of the apgar exam of the first minute (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>apgar_5_minuto</code>	"all" or a character vector with the value of the apgar exam of the fifth minute (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>peso_ao_nascer</code>	"all" or a character vector with the birth weight (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>anomalia_congenita</code>	"all" or a character vector with the indicative of congenital anomaly (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>tipo_anomal_congen</code>	"all" or a character vector with the congenital anomaly type (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use 'sim()' or 'sinasc()' with a named 'filtros' list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sinasc_nv_uf](#)

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  ## Requesting data from the city of Campo Grande/MS
  sinasc_nv_mun(municipio = 500270)
})
options(old_options)
```

sinasc_nv_uf

Scrapes SINASC data from ufs

Description

This function allows the user to retrieve data from SINASC database much in the same way that is done by the online portal. The argument options refer to data from the states unities.

Usage

```
sinasc_nv_uf(uf, linha = "Município", coluna = "Não ativa",
  conteudo = 1, periodo = "last", municipio = "all", cir = "all",
  macrorregiao_de_saude = "all", divisao_admnist_estadual = "all",
  microrregiao_ibge = "all", ride = "all", local_ocorrencia = "all",
  idade_da_mae = "all", instrucao_da_mae = "all", estado_civil_mae = "all",
  duracao_gestacao = "all", tipo_de_gravidez = "all", tipo_de_parto = "all",
  consult_pre_natal = "all", sexo = "all", cor_raca = "all", apgar_1_minuto = "all",
  apgar_5_minuto = "all", peso_ao_nascer = "all", anomalia_congenita = "all",
  tipo_anomal_congen = "all")
```

Arguments

<code>uf</code>	A character of length = 1 with the state's acronym of interest.
<code>linha</code>	A character describing which element will be displayed in the rows of the data.frame. Defaults to "Município".
<code>coluna</code>	A character describing which element will be displayed in the columns of the data.frame. Defaults to "Não ativa".
<code>conteudo</code>	A character of length = 1 with the state's acronym of interest.
<code>periodo</code>	A character vector describing the period of data. Defaults to the last available.
<code>municipio</code>	"all" or a numeric vector with the IBGE's city codes codes to filter the data. Defaults to "all".
<code>cir</code>	"all" or a numeric vector with the CIR's codes to filter the data. Defaults to "all".
<code>macrorregiao_de_saude</code>	"all" or a numeric vector with the Health macro-region's codes to filter the data. Defaults to "all".
<code>divisao_admnist_estadual</code>	"all" or a numeric vector with the State administrative division's codes to filter the data. Defaults to "all".
<code>microrregiao_ibge</code>	"all" or a numeric vector with the IBGE's micro-region codes to filter the data. Defaults to "all".
<code>ride</code>	"all" or a numeric vector with the IBGE's metropolitan-region codes to filter the data. Defaults to "all".
<code>local_ocorrencia</code>	"all" or a character vector with the place of occurrence to filter the data. Defaults to "all".
<code>idade_da_mae</code>	"all" or a character vector with the age range (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>instrucao_da_mae</code>	"all" or a character vector with the mother's instruction (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>estado_civil_mae</code>	"all" or a character vector with the marital status of the mother (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>duracao_gestacao</code>	"all" or a character vector with the marital status of the mother (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
<code>tipo_de_gravidez</code>	"all" or a character vector with the type of pregnancy (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

tipo_de_parto	"all" or a character vector with the Parturition type (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
consult_pre_natal	"all" or a character vector with the amount of prenatal consultation (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
sexo	"all" or a character vector with the gender (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
cor_raca	"all" or a character vector with the color/race (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
apgar_1_minuto	"all" or a character vector with the value of the apgar exam of the first minute (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
apgar_5_minuto	"all" or a character vector with the value of the apgar exam of the fifth minute (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
peso_ao_nascer	"all" or a character vector with the birth weight (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
anomalia_congenita	"all" or a character vector with the indicative of congenital anomaly (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".
tipo_anomal_congen	"all" or a character vector with the congenital anomaly type (written in the same way) or the number corresponding to the order of the option in the online layout to filter the data. Defaults to "all".

Value

The function returns a data frame printed by parameters input.

Lifecycle

This function is deprecated. Use `'sim()'` or `'sinasc()'` with a named `'filtros'` list. The legacy signature is retained for compatibility.

Author(s)

Renato Prado Siqueira <rpradosiqueira@gmail.com>

See Also

[sinasc_nv_mun](#)

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  ## Requesting data from the state of Mato Grosso do Sul
  sinasc_nv_uf(uf = "ms")
})
options(old_options)
```

siscan

Query cancer screening and diagnostic exams from SISCAN

Description

Supports cervical cytology and histology, mammography, and breast cytology and histology by residence, attendance location or patient.

Usage

```
siscan(
  conjunto = "citologia_colo_residencia",
  uf = NULL,
  linha = NULL,
  coluna = NULL,
  conteudo = 1,
  periodo = "last",
  filtros = list()
)
```

Arguments

conjunto	Dataset name listed by ‘datasus_catalogo("sih")’.
uf	Two-letter state abbreviation. ‘NULL’ uses the Brazil form.
linha	Row dimension. ‘NULL’ selects the form’s first dimension.
coluna	Column dimension. ‘NULL’ selects ‘"Não ativa"’.
conteudo	Measure label, raw TABNET value, or one-based index.
periodo	“last” for the latest competence, an exact period label or raw value, a four-digit year (all available competences in that year), or a vector of these values.
filtros	Named list of filters. Names and choices are available from [datasus_opcoes()].

Value

A data frame containing the TABNET result.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  siscan(uf = "MS")
  siscan(
    conjunto = "mamografia_residencia",
    uf = "MS",
    periodo = 2025
  )
})
options(old_options)
```

sisvan

Query legacy nutritional surveillance data from SISVAN

Description

Provides the historical TABNET series for Primary Care users and Bolsa Familia beneficiaries. These are legacy series and should not be interpreted as the current SISVAN coverage.

Usage

```
sisvan(
  conjunto = "atencao_basica",
  uf = NULL,
  linha = NULL,
  coluna = NULL,
  conteudo = 1,
  periodo = "last",
  filtros = list()
)
```

Arguments

conjunto	Dataset name listed by ‘datasus_catalogo("sih")’.
uf	Two-letter state abbreviation. ‘NULL’ uses the Brazil form.
linha	Row dimension. ‘NULL’ selects the form’s first dimension.
coluna	Column dimension. ‘NULL’ selects “Não ativa”.

conteudo	Measure label, raw TABNET value, or one-based index.
periodo	"last" for the latest competence, an exact period label or raw value, a four-digit year (all available competences in that year), or a vector of these values.
filtros	Named list of filters. Names and choices are available from [datasus_opcoes()].

Value

A data frame containing the TABNET result.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  sisvan(uf = "MS")
  sisvan(conjunto = "bolsa_familia", uf = "MS")
})
options(old_options)
```

sivep_gripe

Read SIVEP-Gripe severe acute respiratory syndrome microdata

Description

Read SIVEP-Gripe severe acute respiratory syndrome microdata

Usage

```
sivep_gripe(
  ano = "last",
  formato = "CSV",
  destino = NULL,
  cache = TRUE,
  atualizar = FALSE,
  n_max = Inf,
  ...
)
```

Arguments

ano	Dataset year or "last".
formato	"CSV" or "JSON".
destino	Optional destination file or existing directory.

cache	Whether to reuse the local cache.
atualizar	Whether to force a new metadata query and download.
n_max	Maximum number of CSV rows to read.
...	Additional arguments passed to the underlying reader.

Value

The parsed OpenDataSUS resource.

Examples

```
old_options <- options(
  datasus.timeout = 5,
  datasus.download_timeout = 15,
  datasus.max_tries = 1
)
try({
  srag <- sivep_gripe(ano = 2025, n_max = 1000)
})
options(old_options)
```

taxa_incidencia	<i>Calculate grouped incidence rates</i>
-----------------	--

Description

Calculate grouped incidence rates

Usage

```
taxa_incidencia(
  dados,
  casos,
  populacao,
  grupo = NULL,
  multiplicador = 1e+05,
  confianca = NULL,
  na_rm = FALSE,
  zero_denominador = c("na", "erro")
)
```

Arguments

dados	A non-empty data frame.
casos	Name of the incident cases column.
populacao	Name of the population or person-time denominator column.

grupo	Optional character vector naming grouping columns.
multiplicador	Positive rate scale, default 100,000.
confianca	Optional confidence level. Exact intervals are available for rates, proportions and case fatality, but not for ratios.
na_rm	Whether rows with a missing numerator or denominator should be removed pair-wise within each group. A group containing no complete row remains missing.
zero_denominador	How to handle zero denominators: "na" returns 'NA', while "erro" stops.

Value

A data frame with aggregated counts and 'taxa_incidencia'.

Examples

```
dados <- data.frame(ano = c(2024, 2024), casos = c(10, 20),
                    populacao = c(50000, 50000))
taxa_incidencia(dados, "casos", "populacao", grupo = "ano")
```

taxa_mortalidade	<i>Calculate grouped mortality rates</i>
------------------	--

Description

Calculate grouped mortality rates

Usage

```
taxa_mortalidade(
  dados,
  obitos,
  populacao,
  grupo = NULL,
  multiplicador = 1e+05,
  confianca = NULL,
  na_rm = FALSE,
  zero_denominador = c("na", "erro")
)
```

Arguments

dados	A non-empty data frame.
obitos	Name of the deaths column.
populacao	Name of the population denominator column.
grupo	Optional character vector naming grouping columns.

multiplicador	Positive rate scale, default 100,000.
confianca	Optional confidence level. Exact intervals are available for rates, proportions and case fatality, but not for ratios.
na_rm	Whether rows with a missing numerator or denominator should be removed pair-wise within each group. A group containing no complete row remains missing.
zero_denominador	How to handle zero denominators: "na" returns 'NA', while "erro" stops.

Value

A data frame with aggregated counts and 'taxa_mortalidade'.

Examples

```
dados <- data.frame(ano = c(2024, 2024), obitos = c(3, 7),
                    populacao = c(5000, 5000))
taxa_mortalidade(dados, "obitos", "populacao", grupo = "ano")
```

validar_codigo_ibge	<i>Validate IBGE territorial codes</i>
---------------------	--

Description

Validate IBGE territorial codes

Usage

```
validar_codigo_ibge(codigo, nivel = c("municipio", "uf", "regiao"))
```

Arguments

codigo	Vector of territorial identifiers.
nivel	Territorial level: "municipio", "uf" or "regiao".

Value

A logical vector. Missing and unknown values return 'FALSE'.

Examples

```
validar_codigo_ibge(c("500270", "999999"))
validar_codigo_ibge(c("MS", "XX"), "uf")
```

Index

* SIM

- sim_evita10_bruf, [50](#)
- sim_evita10_mun, [52](#)
- sim_evita10_uf, [55](#)
- sim_evitb10_bruf, [57](#)
- sim_evitb10_mun, [59](#)
- sim_evitb10_uf, [62](#)
- sim_inf10_bruf, [64](#)
- sim_inf10_mun, [67](#)
- sim_inf10_uf, [71](#)
- sim_obt10_bruf, [74](#)
- sim_obt10_mun, [77](#)
- sim_obt10_uf, [80](#)

* SINASC

- sinasc_nv_bruf, [88](#)
- sinasc_nv_mun, [90](#)
- sinasc_nv_uf, [93](#)

* causas

- sim_evita10_bruf, [50](#)
- sim_evita10_mun, [52](#)
- sim_evita10_uf, [55](#)
- sim_evitb10_bruf, [57](#)
- sim_evitb10_mun, [59](#)
- sim_evitb10_uf, [62](#)

* child

- sim_inf10_bruf, [64](#)
- sim_inf10_mun, [67](#)
- sim_inf10_uf, [71](#)

* datasus

- sim_evita10_bruf, [50](#)
- sim_evita10_mun, [52](#)
- sim_evita10_uf, [55](#)
- sim_evitb10_bruf, [57](#)
- sim_evitb10_mun, [59](#)
- sim_evitb10_uf, [62](#)
- sim_inf10_bruf, [64](#)
- sim_inf10_mun, [67](#)
- sim_inf10_uf, [71](#)
- sim_obt10_bruf, [74](#)

- sim_obt10_mun, [77](#)
- sim_obt10_uf, [80](#)
- sinasc_nv_bruf, [88](#)
- sinasc_nv_mun, [90](#)
- sinasc_nv_uf, [93](#)

* evitáveis

- sim_evita10_bruf, [50](#)
- sim_evita10_mun, [52](#)
- sim_evita10_uf, [55](#)
- sim_evitb10_bruf, [57](#)
- sim_evitb10_mun, [59](#)
- sim_evitb10_uf, [62](#)

* mortality

- sim_inf10_bruf, [64](#)
- sim_inf10_mun, [67](#)
- sim_inf10_uf, [71](#)

adicionar_territorio, [5](#)

calcular_indicador, [6](#)

calcular_taxa, [7](#)

calendario_epidemiologico, [8](#)

cnes, [8](#)

completar_territorios, [9](#)

datasus (datasus-package), [4](#)

datasus-package, [4](#)

datasus_catalogo, [11](#)

datasus_dicionario, [11](#)

datasus_opcoes, [12](#)

datasus_padronizar, [13](#)

datasus_proveniencia, [14](#)

datasus_territorios, [14](#)

datasus_validar_esquema, [15](#)

esavi, [16](#)

esus_sindrome_gripal, [17](#)

extrair_codigo_ibge, [18](#)

financiamento_sus, [19](#)

intervalo_taxa, 20

juntar_populacao, 21

letalidade, 22

media_movel, 23

microdados_arquivos, 24

microdados_baixar, 25

microdados_catalogo, 26

microdados_ler, 27

normalizar_codigo_ibge, 28

ocupacao_hospitalar, 29

opendatasus_arquivos, 30

opendatasus_baixar, 31

opendatasus_catalogo, 33

opendatasus_ler, 34

opendatasus_processar, 35

opendatasus_recursos, 37

padronizar_idade, 37

pni_doses, 39

pni_imunizacoes, 40

populacao_padrao, 41

populacao_residente, 42

proporcao, 43

semana_epidemiologica, 44

sia_producao, 45

sih_microdados, 46

sih_morbidade, 46

sih_producao, 48

sim, 49

sim_evita10_bruf, 50, 58

sim_evita10_mun, 52, 61, 66, 70

sim_evita10_uf, 55, 63, 73

sim_evitb10_bruf, 57

sim_evitb10_mun, 59

sim_evitb10_uf, 62

sim_inf10_bruf, 64

sim_inf10_mun, 67

sim_inf10_uf, 71

sim_microdados, 74

sim_obt10_bruf, 74

sim_obt10_mun, 56, 77, 82

sim_obt10_uf, 80

sinan, 82

sinan_dengue, 84

sinan_mpox, 85

sinasc, 86

sinasc_microdados, 87

sinasc_nv_bruf, 88

sinasc_nv_mun, 90, 95

sinasc_nv_uf, 52, 54, 76, 79, 90, 93, 93

siscan, 96

sisvan, 97

sivep_gripe, 98

taxa_incidencia, 99

taxa_mortalidade, 100

validar_codigo_ibge, 101