

Package ‘zigimports’

October 27, 2026

Type Package

Title Call 'Zig' Code from R

Version 0.1.0

Description Loads shared libraries compiled from 'Zig' ('.so' files on Linux, '.dll' files on Windows) and binds their exported functions to R functions. Arguments are passed by value using the native calling convention, so functions with mixed integer, double, logical, string and vector arguments and with return values can be called. Also compiles and runs 'Zig' code directly from R. Compiling code requires the 'Zig' compiler.

URL <https://github.com/lokop5116/zigimports>

BugReports <https://github.com/lokop5116/zigimports/issues>

License GPL-3

Encoding UTF-8

Depends R (>= 3.5.0)

SystemRequirements 'Zig' compiler (>= 0.11), only needed for zig_call() and to build libraries

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

RoxygenNote 7.3.2

NeedsCompilation yes

Author Lakshya Sharma [aut, cre],
Amrit Pal [aut]

Maintainer Lakshya Sharma <lakshya6115@gmail.com>

Repository CRAN

Date/Publication 2026-10-27 15:20:02 UTC

Contents

zigimports-package	2
zig_bind	2
zig_call	4
zig_load	6
Index	7

zigimports-package	<i>zigimports: Call 'Zig' Code from R</i>
--------------------	---

Description

Load shared libraries compiled from 'Zig' (.so on Linux, .dll on Windows) with [zig_load](#), bind exported functions with [zig_bind](#), and compile and run 'Zig' code from R with [zig_call](#).

Author(s)

Maintainer: Firstname Lastname <author@example.com>
Authors:
• Coauthor Name

zig_bind	<i>Bind an exported Zig function to an R function</i>
----------	---

Description

Looks up a function exported from a library loaded with [zig_load](#) and returns an ordinary R function that calls it. Arguments are passed by value with the native C calling convention, so functions with mixed argument types, such as `export fn add(a: i32, b: f64) f64`, work as expected.

Usage

```
zig_bind(lib, name, args = NULL, returns = "void")
```

Arguments

lib	A <code>zig_lib</code> object returned by zig_load .
name	Name of the exported Zig function.
args	Character vector with the type of each argument, or <code>NULL</code> for a function without arguments.
returns	Return type of the Zig function (default <code>"void"</code>).

Details

Supported types (a Zig-style or R-style name may be used):

Type	Zig	R value
"i32"	i32, c_int	single integer
"f64"	f64	single double
"bool"	bool	single logical
"str"	[*:0]const u8	single string
"ptr_f64"	[*]f64	double vector
"ptr_i32"	[*]i32	integer or logical vector

"void" is also valid as a return type. Functions must be declared with `export fn`, take at most six arguments, and cannot return pointers other than strings. Vector arguments are copied before the call, so the caller's data is never modified; the modified copies are returned (see Value). NA integers are passed as the C value `INT_MIN`. The Zig code runs inside the R process: a crash in Zig crashes R.

Value

A function taking the Zig function's arguments. Calling it returns the Zig return value. If the function has vector arguments, their (possibly modified) copies are returned as a named list: in the "args" attribute of the return value, or as the result itself for a void function.

See Also

[zig_load](#), [zig_call](#)

Examples

```
if (nzchar(Sys.which("zig"))) {
  q <- function(p) shQuote(p, type = if (.Platform$OS.type == "windows") "cmd" else "sh")
  src <- system.file("examples", "mathlib.zig", package = "zigimports")
  tmp <- tempfile("zigimports_ex_")
  dir.create(tmp)
  out <- file.path(tmp, paste0("mathlib", .Platform$dynlib.ext))
  status <- system2("zig", c("build-lib", q(src), "-dynamic", "-O", "ReleaseFast",
                             paste0("-femit-bin=", q(out)),
                             "--cache-dir", q(file.path(tmp, "c")),
                             "--global-cache-dir", q(file.path(tmp, "g"))),
                    stdout = FALSE, stderr = FALSE)
  if (status == 0L && file.exists(out)) {
    lib <- zig_load(out)
    add <- zig_bind(lib, "add", args = c("i32", "f64"), returns = "f64")
    add(2L, 0.5)
    total <- zig_bind(lib, "total", args = c("ptr_f64", "i32"), returns = "f64")
    total(c(1, 2, 3), 3L)
    dyn.unload(lib$path)
  }
  unlink(tmp, recursive = TRUE)
}
```

zig_call

*Compile and run Zig code from R***Description**

Compiles 'Zig' source into a temporary shared library with the zig compiler, loads it, calls it, and cleans up. Requires Zig (0.11 or later) to be installed and on the PATH, or located through `options(zigimports.zig = ...)` or the `ZIGIMPORTS_ZIG` environment variable. All build files are written to a temporary directory.

Usage

```
zig_call(
  code,
  ...,
  fn = NULL,
  args = NULL,
  returns = "void",
  optimize = c("ReleaseFast", "ReleaseSafe", "ReleaseSmall", "Debug"),
  flags = character(),
  zig = NULL,
  keep = FALSE,
  verbose = FALSE
)
```

Arguments

<code>code</code>	Zig source code (character string), or path to a .zig file.
<code>...</code>	Arguments passed to the Zig function. Must be named in snippet mode.
<code>fn</code>	Name of the exported function to call, or NULL for snippet mode.
<code>args</code>	Argument types (function mode only); see zig_bind .
<code>returns</code>	Return type of the function or snippet.
<code>optimize</code>	Zig optimisation mode.
<code>flags</code>	Extra command-line flags for zig build-lib, e.g. "-lc".
<code>zig</code>	Path or name of the Zig compiler. Defaults to <code>getOption("zigimports.zig")</code> , then <code>ZIGIMPORTS_ZIG</code> , then "zig".
<code>keep</code>	If TRUE, keep the temporary build directory and report its location.
<code>verbose</code>	If TRUE, show the generated source and compiler command.

Details

There are two modes:

- **Function mode** (fn given): code is a complete Zig source (or the path to a .zig file) that defines export fn <fn>. The function is called with ... Argument types are given by args; if NULL they are inferred (length-1 double, integer, logical and string values are passed by value, longer vectors as pointers). Use args when a length-1 vector must be passed as a pointer.
- **Snippet mode** (fn = NULL): code is just a function body. Each named argument in ... becomes a Zig parameter with that name: a pointer for numeric, integer and logical vectors ([*]f64 or [*]i32) and [*:0]const u8 for a single string. The vector lengths are available as zig_lens[i] in argument order, and std is already imported. The body can return a value if returns is set.

See [zig_bind](#) for the supported types and conventions.

Value

As for functions created by [zig_bind](#): the Zig return value (with the modified vector arguments in the "args" attribute), or, for returns = "void", a named list of the modified vector arguments (invisible NULL if there are none).

See Also

[zig_load](#), [zig_bind](#)

Examples

```
if (nzchar(Sys.which("zig"))) {
  # Function mode: mixed argument types and a return value
  src <- "export fn add(a: i32, b: f64) f64 {
    return @as(f64, @floatFromInt(a)) + b;
  }"
  zig_call(src, fn = "add", args = c("i32", "f64"), returns = "f64",
           2L, 0.5)
}

if (nzchar(Sys.which("zig"))) {
  # Snippet mode: double every element of a vector
  zig_call("
    var i: usize = 0;
    while (i < @as(usize, @intCast(zig_lens[0]))) : (i += 1) x[i] *= 2;
    ", x = c(1, 2, 3))
}
```

zig_load

*Load a Zig shared library***Description**

Loads a shared library produced by the 'Zig' compiler (a .so file on Linux or a .dll file on Windows) so that its exported functions can be bound with [zig_bind](#).

Usage

```
zig_load(path)
```

Arguments

path Path to the compiled shared library.

Value

An object of class "zig_lib": a list with the normalised path, the library name, and the dll handle returned by [dyn.load](#).

See Also

[zig_bind](#), [zig_call](#)

Examples

```
if (nzchar(Sys.which("zig"))) {
  q <- function(p) shQuote(p, type = if (.Platform$OS.type == "windows") "cmd" else "sh")
  src <- system.file("examples", "mathlib.zig", package = "zigimports")
  tmp <- tempfile("zigimports_ex_")
  dir.create(tmp)
  out <- file.path(tmp, paste0("mathlib", .Platform$dynlib.ext))
  status <- system2("zig", c("build-lib", q(src), "-dynamic", "-O", "ReleaseFast",
                             paste0("-femit-bin=", q(out)),
                             "--cache-dir", q(file.path(tmp, "c")),
                             "--global-cache-dir", q(file.path(tmp, "g"))),
                    stdout = FALSE, stderr = FALSE)
  if (status == 0L && file.exists(out)) {
    lib <- zig_load(out)
    print(lib)
    dyn.unload(lib$path)
  }
  unlink(tmp, recursive = TRUE)
}
```

Index

`dyn.load`, [6](#)

`zig_bind`, [2](#), [2](#), [4–6](#)

`zig_call`, [2](#), [3](#), [4](#), [6](#)

`zig_load`, [2](#), [3](#), [5](#), [6](#)

`zigimports` (`zigimports-package`), [2](#)

`zigimports-package`, [2](#)