

# Package ‘PathwayVote’

January 17, 2026

**Title** Robust Pathway Enrichment for DNA Methylation Studies Using Ensemble Voting

**Version** 0.1.3

**Description** Performs pathway enrichment analysis using a voting-based framework that integrates CpG–gene regulatory information from expression quantitative trait methylation (eQTM) data. For a grid of top-ranked CpGs and filtering thresholds, gene sets are generated and refined using an entropy-based pruning strategy that balances information richness, stability, and probe bias correction. In particular, gene lists dominated by genes with disproportionately high numbers of CpG mappings are penalized to mitigate active probe bias—a common artifact in methylation data analysis. Enrichment results across parameter combinations are then aggregated using a voting scheme, prioritizing pathways that are consistently recovered under diverse settings and robust to parameter perturbations.

**License** MIT + file LICENSE

**Encoding** UTF-8

**Depends** R (>= 4.0.0)

**Imports** harmonicmeanp, AnnotationDbi, clusterProfiler, future, furrr, methods, parallelly

**Suggests** GO.db, org.Hs.eg.db, reactome.db, openxlsx

**RoxygenNote** 7.3.2

**NeedsCompilation** no

**Author** Yinan Zheng [aut, cre] (ORCID: <<https://orcid.org/0000-0002-2006-7320>>)

**Maintainer** Yinan Zheng <y-zheng@northwestern.edu>

**Repository** CRAN

**Date/Publication** 2026-01-17 21:00:02 UTC

## Contents

|                           |   |
|---------------------------|---|
| create_eQTM               | 2 |
| eQTM-class                | 3 |
| getData                   | 3 |
| getMetadata               | 4 |
| pathway_vote              | 4 |
| write_enrich_results_xlsx | 7 |

create\_eQTM

*Create an expression quantitative trait methylation (eQTM) object***Description**

Create an expression quantitative trait methylation (eQTM) object

**Usage**`create_eQTM(data, metadata = list())`**Arguments**

|                   |  |
|-------------------|--|
| <b>data</b>       | A data.frame containing eQTM data with columns: cpg, statistics, p_value, distance, and at least one of entrez or ensembl.   |
| <b>cpg</b>        | Character. CpG probe ID (e.g., "cg00000029"), representing a methylation site.   |
| <b>statistics</b> | Numeric. Test statistic from eQTM association analysis (e.g., correlation coefficient, r-square, regression coefficient, or t-statistic). Can be positive or negative. |
| <b>p_value</b>    | Numeric. P-value associated with the test statistic, must be between 0 and 1.  |
| <b>distance</b>   | Numeric. Genomic distance (in base pairs) between the CpG and the associated gene's transcription start site (TSS). Must be non-negative.                              |
| <b>entrez</b>     | Character. Entrez gene ID of the associated gene. At least one of entrez or ensembl must be provided.  |
| <b>ensembl</b>    | Character. Ensembl gene ID of the associated gene. At least one of entrez or ensembl must be provided.   |
| <b>metadata</b>   | A list of metadata (optional).   |

**Value**

An eQTM object.

**Examples**

```
data <- data.frame(
  cpg = c("cg000001", "cg000002"),
  statistics = c(2.5, -1.8),
  p_value = c(0.01, 0.03),
  distance = c(50000, 80000),
  entrez = c("673", "1956")
)
eqtm_obj <- create_eQTM(data)
```

---

**eQTM-class***Expression quantitative trait methylation (eQTM) Class*

---

**Description**

A class to store eQTM data for pathway analysis. eQTM stands for Expression Quantitative Trait Methylation.

**Slots**

**data** A data.frame containing eQTM data with columns: cpg, statistics, p\_value, distance, and at least one of entrez or ensembl.

**metadata** A list of metadata (e.g., data source, time point). Reserved for future use.

---

**getData***Get expression quantitative trait methylation (eQTM) Data*

---

**Description**

Retrieve the eQTM data.frame from an eQTM object.

**Usage**

```
getData(object)

## S4 method for signature 'eQTM'
getData(object)
```

**Arguments**

**object** An eQTM object.

**Value**

A data.frame stored in the object.

---

|             |  |
|-------------|--|
| getMetadata | <i>Get expression quantitative trait methylation (eQTM) Metadata</i> |
|-------------|--|

---

### Description

Retrieve the metadata list from an eQTM object.

### Usage

```
getMetadata(object)

## S4 method for signature 'eQTM'
getMetadata(object)
```

### Arguments

object            An eQTM object.

### Value

A list containing metadata.

---

|              |   |
|--------------|---|
| pathway_vote | <i>Pathway Voting-Based Enrichment Analysis</i> |
|--------------|---|

---

### Description

Performs pathway enrichment analysis using a voting-based framework that integrates CpG-gene regulatory information from expression quantitative trait methylation (eQTM) data. For a grid of top-ranked CpGs and filtering thresholds, gene sets are generated and refined using an entropy-based pruning strategy that balances information richness, stability, and probe bias correction. In particular, gene lists dominated by genes with disproportionately high numbers of CpG mappings are penalized to mitigate active probe bias, a common artifact in methylation data analysis. Enrichment results across parameter combinations are then aggregated using a voting scheme, prioritizing pathways that are consistently recovered under diverse settings and robust to parameter perturbations.

### Usage

```
pathway_vote(
  cpg_input,
  eQTM,
  databases = c("Reactome"),
  k_grid = NULL,
  stat_grid = NULL,
  distance_grid = NULL,
```

```

grid_size = 5,
overlap_threshold = 0.7,
fixed_prune = NULL,
min_genes_per_hit = 2,
readable = FALSE,
workers = NULL,
verbose = FALSE
)

```

## Arguments

|                   |   |
|-------------------|---|
| cpg_input         | A data.frame containing CpG-level results or identifiers. The first column must contain CpG IDs, which can be Illumina probe IDs (e.g., "cg00000029") for array-based data, or genomic coordinates (e.g., "chr1:10468" or "chr1:10468:+") for sequencing-based data. These IDs will be matched against the eQTM object. Optionally, a second column may provide a ranking metric. If supplied, this must be: (i) the complete set of raw p-values from association tests (required for automatic k_grid generation), or (ii) an alternative metric such as t-statistics or feature importance scores, in which case k_grid must be specified manually. If no ranking information is provided, all input CpGs are used directly and k_grid is ignored. |
| eQTM              | An eQTM object containing CpG-gene linkage information, created by the create_eQTM() function. This object provides the CpG-to-gene mapping used for pathway inference. Please make sure the CpG IDs used here match those in cpg_input.  |
| databases         | A character vector of pathway databases. Supporting: "Reactome", "KEGG", and "GO".  |
| k_grid            | A numeric vector specifying the top-k CpGs used for gene set construction. If NULL, the grid is inferred automatically, but this requires that cpg_input contains: (i) the complete set of CpGs tested (first column), and (ii) raw p-values from the association test (second column). If these conditions are not satisfied, or if alternative ranking metrics are provided (e.g., t-statistics, feature importance scores), then k_grid must be specified manually.  |
| stat_grid         | A numeric vector of eQTM statistic thresholds. If NULL, generated based on quantiles of the observed distribution.  |
| distance_grid     | A numeric vector of CpG-gene distance thresholds (in base pairs). If NULL, generated based on quantiles of the observed distribution.   |
| grid_size         | Integer. Number of values in each grid when auto-generating. Default is 5.  |
| overlap_threshold | Numeric between 0 and 1. Controls the maximum allowed Jaccard similarity between gene lists during redundancy filtering. Default is 0.7, which provides robust and stable results across a variety of simulation scenarios.   |
| fixed_prune       | Integer or NULL. Minimum number of votes to retain a pathway. If NULL, will use cuberoot(N) where N is the number of total enrichment runs.   |
| min_genes_per_hit | Minimum number of genes a pathway must include to be considered. Default is 2.  |

|          |   |
|----------|---|
| readable | Logical. Whether to convert Entrez IDs to gene symbols in enrichment results. |
| workers  | Optional integer. Number of parallel workers. If NULL, use 2 logical cores.   |
| verbose  | Logical. Whether to print progress messages.                                  |

### Value

A named list of data.frames containing:

- Enrichment results for each selected database (e.g., ‘Reactome’, ‘KEGG’, ‘GO’). Each data.frame contains columns: ‘ID’, ‘p.adjust’, ‘Description’, and ‘geneID’.
- ‘CpG\_Gene\_Mapping’: A data.frame showing the CpG-Gene relationships for genes identified in the significantly enriched pathways, limited to the CpGs present in the input ‘cpg\_input’.

### Examples

```
set.seed(123)

# Simulated EWAS result: a mix of signal and noise
n_cpg <- 500
ewas <- data.frame(
  cpg = paste0("cg", sprintf("%08d", 1:n_cpg)),
  p_value = c(runif(n_cpg*0.1, 1e-9, 1e-5), runif(n_cpg*0.2, 1e-3, 0.05), runif(n_cpg*0.7, 0.05, 1))
)

# Corresponding eQTM mapping (some of these CpGs have gene links)
signal_genes <- c("5290", "673", "1956", "7157", "7422")
background_genes <- as.character(1000:9999)
entrez_signal <- sample(signal_genes, n_cpg * 0.1, replace = TRUE)
entrez_background <- sample(setdiff(background_genes, signal_genes), n_cpg * 0.9, replace = TRUE)

eqtm_data <- data.frame(
  cpg = ewas$cpg,
  statistics = rnorm(n_cpg, mean = 2, sd = 1),
  p_value = runif(n_cpg, min = 0.001, max = 0.05),
  distance = sample(1000:10000, n_cpg, replace = TRUE),
  entrez = c(entrez_signal, entrez_background),
  stringsAsFactors = FALSE
)
eqtm_obj <- create_eQTM(eqtm_data)

# Run pathway voting with minimal settings
## Not run:
results <- pathway_vote(
  cpg_input = ewas,
  eQTM = eqtm_obj,
  databases = c("GO", "KEGG", "Reactome"),
  readable = TRUE,
  verbose = TRUE
)
head(results$GO)
head(results$KEGG)
```

```
head(results$Reactome)

# Export results to Excel (optional)
library(openxlsx)
write_enrich_results_xlsx(results, "pathway_vote_results.xlsx")

## End(Not run)
```

---

**write\_enrich\_results\_xlsx**

*Export Enrichment Results to Excel*

---

**Description**

Exports the results from ‘pathway\_vote’ to a multi-sheet Excel file. Validates that the input is a list, checks for the ‘openxlsx’ package, and handles sheet naming to comply with Excel limitations.

**Usage**

```
write_enrich_results_xlsx(results, file = "enrich_results.xlsx")
```

**Arguments**

|         |   |
|---------|---|
| results | A named list of data.frames (e.g., output from ‘pathway_vote’). |
| file    | Character. Output file path (e.g., "enrich_results.xlsx").      |

**Value**

Invisible. The path to the saved file.

**Examples**

```
## Not run:
# Assuming `res` is the output from pathway_vote(...)
write_enrich_results_xlsx(res, "my_results.xlsx")

## End(Not run)
```

# Index

create\_eQTM, [2](#)  
eQTM-class, [3](#)  
getData, [3](#)  
getData, eQTM-method (getData), [3](#)  
getMetadata, [4](#)  
getMetadata, eQTM-method (getMetadata), [4](#)  
pathway\_vote, [4](#)  
write\_enrich\_results\_xlsx, [7](#)